



"CANON" PLASTIC CABLE BUSHES - "EZ" SERIES -

ITEM: YL 6,3-9,8-7-2 PA66-RV NERE

Codice EZ: 344930


Material: polyethylene (PE-LD), polyamide 6 (PA 6), polyamide 66 (PA 66), glass fiber reinforced polyamide 66 (PA 66-RV) or glass fiber reinforced polybutylene terephthalate (PBT-RV).

Color: natural, white or black.

Use temperature: max +60°C (PE-LD), max +100°C (PA 6), max +105°C (PA 66), max +120°C (PA 66-RV), max +150°C (PBT -RV).

Flammability: UL94-HB (PA 66-RV) flame-retardant, UL94-V2 (PA 6 and PA 66) flame-retardant and self-extinguishing, UL94-V0 flame retardant and self-extinguishing (PBT-RV).

Features: they are generally used to insulate and protect electrical cables. The YL type bushings can be used in conjunction with the CYL type bushings, with the same $\varnothing G$, to obtain a clip fixing.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	$\varnothing A$ mm	$\varnothing B$ mm	$\varnothing G$ mm	H mm	H1 mm	pack pcs.
YL 6,3-9,8-7-2 PA66-RV NERE	black	PA 66-RV	6,3	20	9,8	7	2	1000

* Bushing also available in gold-colored polyethylene.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

