



## "CANON" PLASTIC CABLE BUSHES - "EZ" SERIES -

### ITEM: YL 6,3-9,8-8-3 PA66-RV NERE

**Codice EZ: 344939**


Material: polyethylene (PE-LD), polyamide 6 (PA 6), polyamide 66 (PA 66), glass fiber reinforced polyamide 66 (PA 66-RV) or glass fiber reinforced polybutylene terephthalate (PBT-RV).

Color: natural, white or black.

Use temperature: max +60°C (PE-LD), max +100°C (PA 6), max +105°C (PA 66), max +120°C (PA 66-RV), max +150°C (PBT -RV).

Flammability: UL94-HB (PA 66-RV) flame-retardant, UL94-V2 (PA 6 and PA 66) flame-retardant and self-extinguishing, UL94-V0 flame retardant and self-extinguishing (PBT-RV).

Features: they are generally used to insulate and protect electrical cables. The YL type bushings can be used in conjunction with the CYL type bushings, with the same  $\varnothing G$ , to obtain a clip fixing.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                              | Color | Material | $\varnothing A$ mm | $\varnothing B$ mm | $\varnothing G$ mm | H mm | H1 mm | pack pcs. |
|-----------------------------------|-------|----------|--------------------|--------------------|--------------------|------|-------|-----------|
| YL 6,3-9,8-8-3<br>PA66-RV<br>NERE | black | PA 66-RV | 6,3                | 20                 | 9,8                | 8    | 3     | 1000      |

\* Bushing also available in gold-colored polyethylene.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

