


CABLE FAIRING PROFILE IN PLASTIC RACK - "PLIOBORD" SERIES -

ITEM: DX 1,5 C

Codice EZ: 140282, CABLE SES-Sterling code: 08260002018.

Material: normal polyethylene (halogen free), flame retardant polyethylene (with halogens).

Color: white and natural.

Use temperature: -50°C / +85°C (normal polyethylene), -50°C / +75°C (flame retardant polyethylene).

Flammability: flame-retardant and self-extinguishing UL94-V2 for the DX CAF profile.

Features: the cable entry profile is applied by hand, without the aid of any tools, and serves for the protection and insulation of cables passing through the sharp edges of sheets or walls. It is very flexible and is suitable for large holes or with irregular shapes.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	specific	A mm	B mm	H mm	H1 mm	frame thickness mm	pack mt.
DX 1,5 C	natural	-	1,5	3,5	3,2	2	1,5	30

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

