



PLASTIC CABLE BUSHINGS WITH MEMBRANE - "HEYCO" SERIES -

Material: polyamide 6/6.


Color: black.

Use temperature: max +105°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: they have good resistance to chemicals and good electrical properties. They absorb vibrations and at the same time offer insulation and mechanical protection to cables and pipes of all kinds. The flexible wedges adapt to any shape of cable or tube with a minimum $\varnothing$ of 7.6 mm and a maximum of 62.7 mm. Thanks to the fastening teeth, these bushings snap into place and adapt to the thickness of the frame up to a maximum indicated in the table.

On request: for quantity, they can be supplied in white or in other colors on sample.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	ØA max mm	ØB mm	H mm	max frame thickness mm	Ø mounting hole mm	pack pcs.
SUB-500	for thin frame	7,6	15,2	6,4	1,6	12,7	500
UB-500	-	7,6	15,2	9,8	3,2	12,7	500
SUB-625	for thin frame	11,1	18,5	6,4	1,6	15,9	500
UB-625	-	11,1	18,3	10,3	3,2	15,9	500
UB-750	-	12,7	21,4	9,9	3,2	19	500
SUB-750	for thin frame	12,7	21,8	6,4	1,6	19,1	500
UB-812	-	12,7	22,6	9,9	3,2	20,6	500
SUB-875	for thin frame	14,2	23,8	6,4	1,6	22,2	500
UB-875	-	14,3	23,8	11,5	3,2	22,2	500
SUB-1000	for thin frame	19	27	6,4	1,6	25,4	500
UB-1000	-	19	27	11,5	3,2	25,4	200
SUB-1093	for thin frame	20,6	29,4	6,4	1,6	27,8	500
UB-1093	-	20,6	29,4	11,5	3,2	27,8	200
UB-1187	-	24,1	31,8	11,5	3,2	30,2	500
UB-1375	-	25,4	37,8	11,5	3,2	34,9	200
UB-1250	-	25,8	33,4	11,5	3,2	31,8	500
UB-1500	-	26,9	40,9	11,4	3,2	38,1	200
UB-1750	-	34,9	47,5	11,8	3,2	44,5	200
UB-2000	-	41,6	54	12,4	3,2	50,8	200
UB-2.5	-	50	66,8	19	6,4	63,5	150
UB-3.0	-	62,7	80	19	6,4	76,2	150

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

