



EX METAL CABLE GLANDS FOR NON ARMORED CABLES - "EZ" SERIES (NPT THREAD)

ITEM: EXD NR-1F T34.13.20

Codice EZ: request the code from our sales office

Material: pressacavi in ottone nichelato, guarnizione in Neoprene, rondella O-Ring in grafite (-200°C / +450°C).

Gasket: -OT (otturata).

Use temperature: -60°C / +80°C

IP protection: IP 66, IP 68.

Ex protection: Ex db / Ex eb / Ex tb.

Group: IIA, IIB, IIC e IIIA, IIIB, IIIC.


Category: 2 e 3.

Area: G (Gas) 1 e 2 / D (Polveri) 21 e 22.

Regulations and Certifications: IEC, IECEx, CE, EAC Ex, PCEC, INMETRO, IECEx LCIE 16.0026X, EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-7, EN/IEC 60079-31, LCIE 16 ATEX 3030 X, BVC16.5800-X, CE19.5255X, TR CU EX RU C-FR.BH02.B.00558/20.

Features: pressacavi conformi IECEx per cavi non armati, in esecuzione Ex db / Ex eb / Ex tb. In tabella, la "misura pressacavo" è utile per l'abbinamento con l'accessorio "CPPT" che è un protettore in plastica per pressacavi.

On request: questi pressacavi sono disponibili in ottone grezzo e in acciaio inox 316L. Sono anche disponibili con la guarnizione in Viton (-20°C / +200°C) per resistere alle alte temperature. Infine, sono disponibili con certificazione GOST.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	Ø est. min - max cable mm	key mm	H1 mm	H2 mm	cable gland measurement	pack pcs.
EXD NR-1F T34.13.20	NPT	3/4"	13 - 20	40	39,5	21	25L	1

NB: if in the table, in the "key" column, there are two dimensions separated by "/" (example: 20/24), the first dimension corresponds to the HEAD of the cable gland, while the second to the BODY. In the case of a single size, it corresponds to both parties.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

