

METAL CABLE GLANDS WITH ANTI-TEAR CLAMP AND ROUNDED EDGE - "EZ" SERIES (PG THREAD)

ITEM: MOS-ST PG29.24.26

Codice EZ: 164224


Material: pressacavo in ottone nichelato, rondelle in acciaio zincato, -ST caoutchouc 55 Sh A, -CP caoutchouc 55 Sh A, -CPN Neoprene 55 Sh A.

Gasket: -ST (standard), -CP / -CPN (a "cipolla")

Use temperature: MOS-ST -40°C / +60°C, MOS-CP -40°C / +60°C, MOS-CPN -25°C / +100°C

IP protection: IP 65

Features: pressacavi con bordo arrotondato in testa e con morsetto antistrappo ed antitorsione. Si distinguono per il funzionamento concentrico del morsetto che mantiene il cavo centrato nel pressacavo.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Gasket	thread pitch	thread value	key mm	ØA est. min - max cable mm	ØB min - max mm	H1 mm	H2 mm	pack pcs.
MOS-ST PG29.24.26	-ST	PG	29	42/40	24 - 26	19 - 29,5	39	8	20

NB: if in the table, in the "key" column, there are two dimensions separated by "/" (example: 20/24), the first dimension corresponds to the HEAD of the cable gland, while the second to the BODY. In the case of a single size, it corresponds to both parties.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

