



## COLLARINI IN POLIAMMIDE

Material: polyamide 6.

Color: black.

Use temperature: -40°C / +110°C

Flammability: UL94-HB flame retardant.

Features: these collars are suitable for clamping cables or bundles of cables with Ø 3 - 50 mm. They have good resistance to aging, corrosion, ozone and UV rays and have excellent dielectric properties. They are fixed on the panels with screws.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM  | H mm | ØA mm | ØA1 mm | pack pcs. |
|-------|------|-------|--------|-----------|
| CN 3  | 7    | 3     | 3      | 100       |
| CN 5  | 7    | 5     | 3      | 100       |
| CN 6  | 7    | 6     | 3      | 100       |
| CN 7  | 12   | 7     | 5      | 100       |
| CN 8  | 12   | 8     | 5      | 100       |
| CN 9  | 12   | 9     | 5      | 100       |
| CN 10 | 12   | 10    | 5      | 100       |
| CN 12 | 12   | 12    | 5      | 100       |
| CN 14 | 12   | 14    | 5      | 100       |
| CN 16 | 12   | 16    | 5      | 100       |
| CN 18 | 12   | 18    | 5      | 100       |
| CN 20 | 12   | 20    | 5      | 100       |
| CN 22 | 12   | 22    | 5      | 100       |
| CN 24 | 12   | 24    | 5      | 100       |
| CN 26 | 12   | 26    | 5      | 100       |
| CN 28 | 12   | 28    | 5      | 100       |
| CN 30 | 12   | 30    | 5      | 100       |
| CN 34 | 12   | 34    | 5      | 100       |
| CN 38 | 16   | 38    | 5      | 100       |
| CN 42 | 16   | 42    | 5      | 50        |
| CN 46 | 16   | 46    | 5      | 100       |
| CN 50 | 16   | 50    | 5      | 100       |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

