




SPHERICAL ADHESIVE FEET IN POLYURETHANE

ITEM: N112

Codice EZ: 133646

Material: polyurethane with synthetic rubber adhesive.

Color: transparent, black, gray, brown, white.

Use temperature: -20°C / +80°C

Flammability: UL94-HB flame retardant.

Features: these feet have an excellent finish and are suitable for multiple applications.

They are non-slip, anti-vibration, shockproof, are abrasion resistant and are stain proof. Thanks to the particularly resistant adhesive, suitable for indoor applications, they can be applied to a wide variety of surfaces: aluminum, steel, ceramic, formica, glass, polyethylene, polypropylene, vinyl, painted surfaces, etc. They do not contain plasticizers, oils or fillers. The transparent feet are almost invisible when used on glass or otherwise transparent surfaces. It is advisable to keep them at a temperature of + 21/27 ° C max. They come in folders from which they can be easily detached.

Application instructions: it is recommended to apply the foot at a temperature of + 21/27 ° C max, not to touch the adhesive with your fingers and to clean the surface on which it will be applied well. The surface should be smooth, non-porous, clean, dry and free of debris, oils and solvents. Then, place the foot and press firmly; subsequently, the foot cannot be repositioned without damaging the adhesive.

On request: all the feet can be supplied with acrylic adhesive (temperature of use: -40°C / +150°C), very resistant and suitable for outdoor applications. Some items can be made of a special "soft polyurethane", particularly soft and flexible, which allows them to more effectively cushion the blows and, consequently, to reduce the sound due to impact. They are mainly used in furniture doors and drawers and have the ability to absorb more than 50% of the impact force. They are made only in transparent color.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	ØB mm	ØB1 mm	H mm	No. of folders	N° feet per folder	pack pcs.
N112	black	9,5	-	3,8	5	200	1440

* This foot can be made of "Soft Polyurethane", which is particularly soft and flexible, which allows you to more effectively cushion blows and reduce the sound due to impact. It is sold in quantities greater than that indicated in the table.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

