



IP 67 - "IP-STOP" - (FOR METRIC HOLE)

Material: Halogen-free EPDM.

Color: light gray Ral 7035, dark gray Ral 7001, black Ral 9005.


Use temperature: -40°C / +110°C

Features: these cable glands exert a discreet anti-traction seal and, above all, ensure an IP 67 seal both on the 2 holes of the cable gland itself and on the wall mounting hole. They have a conical shape whose cone is blocked by a thin membrane. For correct installation, the cable glands must be mounted in the wall hole in the direction of the cone, but, depending on the application, they can be mounted on both sides of the wall so that the cone or the flat base can be seen externally. . Subsequently, the cable is introduced from the side with the open hole and pushed until the membrane breaks and comes out of the cone; finally, the cable must be pulled in the opposite direction by approx. 1 cm. No tools are needed. They are made of EPDM which offers good resistance to atmospheric agents and diluted acids and excellent resistance to UV rays and ozone. Since EPDM is a soft material, these cable glands are the ideal solution for curved surfaces. Please note that these grommets also contain sulfur particles which could potentially have a negative effect on the LEDs.

On request: for quantity, they can be supplied in Chloroprene (black color only), which is a rubber containing halogens, generally more resistant than EPDM and with better resistance to aging. Chloroprene is indicated for the nautical and offshore sector and complies with the DNV (Det Norske Veritas) regulation.

IP protection: IP 67 according to EN 60529 specifications.

Regulations and Certifications: they comply with the SEMKO regulation.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	suitable for hole	Ø est. min - max cable mm	Ø mounting hole mm	frame thickness mm	ØB mm	H mm	H1 mm	pack pcs.
IP-S M1255.4.7	gray RAL 7001	M12	4 - 7	12,5	0,5 - 2	20	12,7	5,4	50
IP-S M1255.4.7-T G	gray RAL 7001	M12	4 - 7	12,5	2 - 5	20	12,7	5,4	50
IP-S M1254.4.7	gray RAL 7035	M12	4 - 7	12,5	0,5 - 2	20	12,7	5,4	50
IP-S M1254.4.7-T G	gray RAL 7035	M12	4 - 7	12,5	2 - 5	20	12,7	5,4	50
IP-S M1256.4.7	black RAL 9005	M12	4 - 7	12,5	0,5 - 2	20	12,7	5,4	50
IP-S M1256.4.7-T G	black RAL 9005	M12	4 - 7	12,5	2 - 5	20	12,7	5,4	50

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





IP-S M1655.5.9	gray RAL 7001	M16	5 - 9	16,5	1 - 4	21	18	10,5	50
IP-S M1655.5.9-T G	gray RAL 7001	M16	5 - 9	16,5	2 - 5	21	18	10,5	50
IP-S M1654.5.9	gray RAL 7035	M16	5 - 9	16,5	1 - 4	21	18	10,5	50
IP-S M1654.5.9-T G	gray RAL 7035	M16	5 - 9	16,5	2 - 5	21	18	10,5	50
IP-S M1656.5.9	black RAL 9005	M16	5 - 9	16,5	1 - 4	21	18	10,5	50
IP-S M1656.5.9-T G	black RAL 9005	M16	5 - 9	16,5	2 - 5	21	18	10,5	50
IP-S M2055.8.13	gray RAL 7001	M20	8 - 13	20,5	1 - 4	25,5	20	12,7	50
IP-S M2054.8.13	gray RAL 7035	M20	8 - 13	20,5	1 - 4	25,5	20	12,7	50
IP-S M2056.8.13	black RAL 9005	M20	8 - 13	20,5	1 - 4	25,5	20	12,7	50
IP-S M2555.11.17	gray RAL 7001	M25	11 - 17	25,5	1 - 4	30,5	21,6	14,5	50
IP-S M2554.11.17	gray RAL 7035	M25	11 - 17	25,5	1 - 4	30,5	21,6	14,5	50
IP-S M2556.11.17	black RAL 9005	M25	11 - 17	25,5	1 - 4	30,5	21,6	14,5	50
IP-S M3255.15.20	gray RAL 7001	M32	15 - 20	32,5	1 - 4	38,5	24,8	17,5	25
IP-S M3254.15.20	gray RAL 7035	M32	15 - 20	32,5	1 - 4	38,5	24,8	17,5	25
IP-S M3256.15.20	black RAL 9005	M32	15 - 20	32,5	1 - 4	38,5	24,8	17,5	25
IP-S M4055.19.28	gray RAL 7001	M40	19 - 28	40,5	1 - 4	48,5	30	20,4	25
IP-S M4054.19.28	gray RAL 7035	M40	19 - 28	40,5	1 - 4	48,5	30	20,4	25
IP-S M4056.19.28	black RAL 9005	M40	19 - 28	40,5	1 - 4	48,5	30	20,4	25
IP-S M5055.27.35	gray RAL 7001	M50	27 - 35	50,5	1 - 4	60,5	35	23,9	10
IP-S M5054.27.35	gray RAL 7035	M50	27 - 35	50,5	1 - 4	60,5	35	23,9	10
IP-S M5056.27.35	black RAL 9005	M50	27 - 35	50,5	1 - 4	60,5	35	23,9	10
IP-S M6355.34.45	gray RAL 7001	M63	34 - 45	63,5	1 - 4	73,5	40	28,9	5

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





IP-S M6354.34.45	gray RAL 7035	M63	34 - 45	63,5	1 - 4	73,5	40	28,9	5
IP-S M6356.34.45	black RAL 9005	M63	34 - 45	63,5	1 - 4	73,5	40	28,9	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

