



CABLE GUIDE FOR "U" HOLE WITH PVC MEMBRANE - "PLIO" SERIES - ITEM: PDGCN-1 14-1475

Codice EZ: 130789

Material: PVC 9542.

Color: black.

Use temperature: -30°C / +70°C

Features: during assembly, the membrane can be drilled according to the diameter of the cable, thus ensuring a good seal against dust. These cable glands have good resistance to low and high temperatures, good resistance to water, diluted acids, alkaline solutions, salts, ozone and UV rays; they have a good resistance to ketones, mineral oils, gasolines, esters and excellent resistance to aging. They have great softness and excellent dielectric properties. The cable glands type PDGC are distinguished from the others by the cross-cut membrane and the straight open side.

Flammability: UL94-HB flame retardant.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	ØA mm	G mm	S mm	L mm	And mm	H mm	M mm	pack pcs.
PDGCN-1 14-1475*	cross-cut membrane	13,5	20	2	24	24	9	1	1000

* Item made with another type of flame retardant compound and with a temperature of use -25°C / +60°C.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

