





CABLE GUIDE WITH PVC MEMBRANE - "PLIO" SERIES -

ี่⊩ITEM: PDG 13,5/M20 BIANCHI

Codice EZ: request the code from our sales office, CABLE SES-Sterling code: 013303530

Material: PVC 9542.

Color: black, gray RAL 7035, white. Use temperature: -30°C / +70°C

Features: during assembly, the membrane can be drilled according to the diameter of the cable, thus ensuring a good seal against dust. Furthermore, the cable gland can also act as a plug to close the holes in the sheets, if the exact exit part of the cable is not known a priori. These cable glands have good resistance to low and high temperatures, good resistance to water, diluted acids, alkaline solutions, salts, ozone and UV rays; they have a good resistance to ketones, mineral oils, gasolines, esters and excellent resistance to aging. They have great softness and excellent dielectric properties.

Flammability: UL94-HB flame retardant.

On request: cable glands in other colors for quantities.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	suitable for	ØA mm	ØG mm	S mm	ØB mm	ØB1 mm	H mm	M mm	pack pcs.
		hole								
PDG	White	M20	13,5	20	2	24	24	7	1	100
13,5/M20										
BIANCHI										

^{*} This grommet, which has a total height (edges + wall thickness) of 8 mm, has edges with heights of 4 and 3 mm.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso





