



CABLE GUIDE WITH IP 67 SEALED MEMBRANE - "IP-PLUG" - (FOR METRIC HOLE)

ITEM: IP-U M2066.6.13

Codice EZ: 131532

Material: TPE/TPE-V0 halogen free.

Color: light gray Ral 7035, black Ral 9005, white Ral 9010.


Use temperature: -50°C / +125°C (TPE cable glands), -40°C / +80°C (TPE-V0 cable glands)

Features: these items can be used both as cable glands and as plugs and in both cases they ensure an IP 67 seal. any tools. They are extremely flexible, they adapt to a wide range of cable diameters and, thanks to an internal protrusion in correspondence with the membrane, they maintain the sealing characteristics unchanged even in the case in which the cable, near the hole, bends at an angle . As they are made of soft TPE they are particularly suitable for applications on curved surfaces. Finally, they are particularly suitable for the lighting sector and in particular for LED luminaires as they are produced in TPE without the addition of sulfur. Flammability: flame retardant and self-extinguishing UL94-V0 (cable glands in TPE-V0)

On request: for quantity, they can be supplied in other colors as per RAL table.

IP protection: IP 67 according to EN 60670-1: 2005 + A1: 2013 specifications.

Regulations and Certifications: SEMKO.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	suitable for hole	Ø est. min - max cable mm	Ø mounting hole mm	frame thickness mm	ØB mm	H mm	H1 mm	pack pcs.
IP-U M2066.6.13	black RAL 9005	TPE	M20	6 - 13	20,5	0,5 - 3	27,5	11	6,75	50

NB: PLEASE NOTE THAT THE EXTERNAL DIAMETER (ØB) AND THE EDGE HEIGHT OF THE CABLE GUIDE (H1) HAVE DIMENSIONS THAT VARY ACCORDING TO THE FRAME THICKNESS.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

