



CABLE GLANDS WITH MEMBRANE ON THE BOTTOM IN PVC - "PLIO" SERIES -

Material: PVC 9542.

Color: black.

Use temperature: -30°C / +70°C

Features: during assembly, the membrane can be drilled according to the diameter of the cable, thus ensuring a good seal against dust. Furthermore, the cable gland can also act as a plug to close the holes in the sheets, if the exact exit part of the cable is not known a priori. The membrane bottom gives the cable gland a better aesthetic impact than the cable gland with the central membrane. These cable glands have good resistance to low and high temperatures, good resistance to water, diluted acids, alkaline solutions, salts, ozone and UV rays; they have a good resistance to ketones, mineral oils, gasolines, esters and excellent resistance to aging. They have great softness and excellent dielectric properties.

Flammability: UL94-HB flame retardant.

On request: cable glands in other colors and in silicone for quantities.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	ØA mm	ØG mm	S mm	ØB mm	H mm	pack pcs.
DKF 5/7/11-3	5	7	3	11	7	100
DKF 5,5/9/12-3	5,5	9	3	12	7	100
DKF 6/9/12-3	6	9	3	12	7	100
DKF 6/14/18-1	6	14	1	18	6	100
DKF 7/14/18-3	7	14	3	18	8	100
DKF 8/14/18-3	8	14	3	18	8	100
DKF 9/12/16-2	9	12	2	16	7	100
DKF 9/14/18-3	9	14	3	18	8	100
DKF 10/18/22-3	10	18	3	22	8	100
DKF 10/18/22-4	10	18	4	22	9	100
DKF 11/18/22-3	11	18	3	22	8	100
DKF 11/18/22-4	11	18	4	22	9	100
DKF 12/18/22-3	12	18	3	22	8	100
DKF 12/18/22-4	12	18	4	22	9	100

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

