







The drawing is indicative and the proportions may not correspond to the table or real dimensions.

CABLE GUIDE WITH MEMBRANE ON THE BOTTOM IN TPE

Material: Halogen-free TPE.

Color: black.

Use temperature: -50°C / +125°C

Features: during assembly, the membrane can be drilled according to the diameter of the cable, thus ensuring a good seal against dust. Furthermore, the cable gland can also act as a plug to close the holes in the sheets, if the exact exit part of the cable is not known a priori. The membrane bottom gives the cable gland a better aesthetic impact than the cable gland with the central membrane.

TPE is a thermoplastic elastomer with excellent characteristics. It is similar to rubber, but is generally used in place of PVC compared to which it is softer, more elastic and has greater resistance to low and high temperatures.

The TPE cable glands have excellent resistance to low and high temperatures, have good resistance to water, ozone, atmospheric agents, acids, aqueous saline solutions, aliphatic and chlorinated solvents and detergents; they have a fair resistance to ketones, mineral oils and petrol and excellent resistance to aging. They are endowed with extreme flexibility and elasticity and good electrical properties. Furthermore, they do not contain halogens.

Flammability: UL94-HB flame retardant.

On request: cable glands in other colors and in silicone for quantities.

ITEM	ØA mm	ØG mm	S mm	ØB mm	H mm	pack pcs.
DKF-TPE 5/7/11-3	5,5	7	3	11	7	100
DKF-TPE 5,5/9/12-3	5,5	9	3	12	7	100
DKF-TPE 6/9/12-3	6	9	3	12	7	100
DKF-TPE 6/14/18-1	6	14	1	18	6	100
DKF-TPE 7/14/18-3	7	14	3	18	8	100
DKF-TPE 8/14/18-3	8	14	3	18	8	100
DKF-TPE 9/12/16-2	9	12	2	16	7	100
DKF-TPE 9/14/18-3	9	14	3	18	8	100
DKF-TPE 10/18/22-3	10	18	3	22	8	100
DKF-TPE 10/18/22-4	10	18	4	22	9	100
DKF-TPE 11/18/22-3	11	18	3	22	8	100
DKF-TPE 11/18/22-4	11	18	4	22	9	100
DKF-TPE 12/18/22-3	12	18	3	22	8	100
DKF-TPE 12/18/22-4	12	18	4	22	9	100

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso



Registro imprese: n° 92394 Tribunale di Milano R.E.A.: 460657 - INTRASTAT: IT 00729140152 Posizione Import: MI 007993



