




UNIVERSAL POLYOLEFIN HEAT SHRINK SHEATH

Material: polyolefin.

Color: black.

Use temperature: -30°C / +105°C

Shrink temperature: > +90°C

Shrink ratio: 2:1

Flammability: flame retardant.

Features: this sheath is flame retardant and suitable for a wide range of industrial applications. It is very economical, flexible and shrinks evenly.

On request: with a surcharge on the price, the sheath is available in sleeves of various lengths.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	ØA min. mm	ØA min. inches	ØA1 max mm	S mm	pack mt.
EPF-A 1,2 NERA	1,2	3/64"	0,6	0,41	200
EPF-A 1,6 NERA	1,6	1/16"	0,8	0,43	200
EPF-A 2,4 NERA	2,4	3/32"	1,2	0,51	200
EPF-A 3,2 NERA	3,2	1/8"	1,6	0,51	200
EPF-A 4,8 NERA	4,7	3/16"	2,4	0,51	200
EPF-A 6,4 NERA	6,4	1/4"	3,2	0,65	150
EPF-A 9,5 NERA	9,5	3/8"	4,8	0,65	150
EPF-A 12,7 NERA	12,7	1/2"	6,4	0,65	100
EPF-A 15,9 NERA	15,9	5/8"	8	0,7	50
EPF-A 19,1 NERA	19,1	3/4"	9,5	0,77	50
EPF-A 25,4 NERA	25,4	1"	12,7	0,89	50
EPF-A 31,8 NERA	31,8	1" 1/4	15,9	0,95	50
EPF-A 38,1 NERA	38,1	1" 1/2	19,1	1	25
EPF-A 50,8 NERA	50,8	2"	25,4	1,1	25

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

