




HEAT SHRINK SLEEVE IN POLYOLEFIN WITH UL STANDARDS, SELF-EXTINGUISHING AND PROFESSIONAL

ITEM: PF-C 15,9 BLU

Codice EZ: request the code from our sales office

Material: polyolefin.

Color: black, white, red, blue, yellow, yellow/green or transparent (the transparent sheath is not flame retardant and is considered "non standard" so the minimum purchase package may be higher than that indicated in the table).

Use temperature: -55°C / +135°C

Shrink temperature: > +90°C

Shrink ratio: 2:1

Flammability: flame retardant and self-extinguishing UL224 VW-1.

Regulations and Certifications: c-UR-us (UL File No. E228117), SAE AMS-DTL-23053/5 Class 3 (transparent sheath: Class 2).

Features: this sheath does not contain cadmium and thanks to its excellent physical and mechanical properties, it is used in professional applications such as electronic and military ones.

On request: with a surcharge on the price, the sheath is available in sleeves of various lengths. For quantity, it can also be made in the following colors: pink, orange, purple, green or brown.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	specific	ØA min. mm	ØA min. inches	ØA1 max mm	S mm	pack mt.
PF-C 15,9 BLU	blue	in skein	15,9	5/8"	8	0,7	100

* Item with use temperature: -55°C / +125°C and certified c-UR-us only.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

