





The drawing is indicative and the proportions may not

correspond to the table or real dimensions.

POLYOLEFIN HEAT SHRINK SLEEVE WITH UL STANDARDS (3: 1 SHRINKAGE)

ITEM: PF-D 24 S TRASPARENTE

Codice EZ: request the code from our sales office

Material: polyolefin.

Color: black, white, red, blue, yellow or transparent (the transparent sheath is not flame retardant and is considered "non-standard" so the minimum purchase package may be higher than that indicated in the table).

Use temperature: -55°C / +135°C Shrink temperature: > +90°C

Shrink ratio: 3:1

Flammability: UL224 flame retardant.

Regulations and Certifications: c-UR-us (UL File No. E228117), SAE

AMS-DTL-23053/5 Class 1 (transparent sheath: Class 2).

Features: this sheath does not contain cadmium and is particularly flexible. It is suitable for multiple applications including electrical insulation, mechanical protection and cable identification.

On request: with a surcharge on the price, the sheath is available in sleeves of various lengths. For quantity, it can also be made in the following colors: pink, orange, purple, green, brown or yellow/green. Furthermore, for quantity, this sheath is available in a new version, in white or yellow, suitable for being printed and for use in the marking of wiring; this sheath can also be supplied completely flat for easier use with suitable printers.

ITEM	Color	specific	ØA min. mm	ØA min. inches	ØA1 max mm	S mm	pack mt.
PF-D 24 S	transparent	in box	24	-	8	1	3
TRASPARENTE							

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso





