



BRAIDED EXPANDABLE PLASTIC SHEATH (UL94-V0)

Material: polyester.

Color: black with gray streaks.

Use temperature: -50°C / +155°C (with peaks up to +200°C)

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: flexible, flame retardant and non-toxic, this sheath adapts perfectly to any bundle of cables and even to irregular shapes. It dissipates heat and humidity and can expand in some cases up to double its nominal diameter. It does not contain halogens and has good resistance to breakage, aging, abrasion, mineral oils, chemical agents, salts, petrol and ultraviolet rays. For cutting it is advisable to use our THERMAL CUTTERS which, while cutting, simultaneously weld the ends of the wires, thus avoiding fraying. In any case, for greater protection of the ends it is always useful to use a sleeve or a cable tie. For a more comfortable grip, the sheath is packed in boxes. The diameter of the sheath is subject to a tolerance of +/- 10%.

On request: for quantity, it can be made in other colors and can be supplied in lengths of your choice.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Nominal Ø mm	expandable up to Ø mm	pack mt.
TCP-V0 3 NERA	3	6	200
TCP-V0 4 NERA	4	8	200
TCP-V0 5 NERA	5	10	100
TCP-V0 6 NERA	6	12	100
TCP-V0 8 NERA	8	16	100
TCP-V0 10 NERA	10	20	100
TCP-V0 12 NERA	12	24	100
TCP-V0 15 NERA	15	30	100
TCP-V0 20 NERA	20	35	50
TCP-V0 25 NERA	25	45	50
TCP-V0 30 NERA	30	50	50
TCP-V0 40 NERA	40	70	50
TCP-V0 50 NERA	50	80	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

