




HEAT SHRINKING AND SELF-WELDING POLYOLEFIN TAPE

Material: halogen-free polyolefin.

Color: black.

Use temperature: -55°C / +105°C

Shrink temperature: > +130°C

Features: this tape is particularly useful in cases of already anchored conductors, of ravines to be insulated, of branches with very different thicknesses and, therefore, where the application of the sheath or heat-shrink sleeve would be problematic. At a temperature above +130°C the tape shrinks onto the cable or object, while at higher temperatures its edges self-weld forming a continuous, insulating and splash-resistant wall. It does not contain halogens and is packaged on a roll.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thickness mm	width mm	pack mt.
A-720	0,07	20	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

