



PLASTIC HEX LOCK NUTS (METRIC THREAD)

Material: polyamide 6 (PA 6) reinforced with glass fiber at 25% for P-CT or 30% for P-CT82.

Color: light gray Ral 7035, dark gray Ral 7001, black Ral 9005.

Use temperature: -30°C / +120°C

Flammability: flame retardant UL94-HB (P-CT)

Features: universal hexagonal lock nut in polyamide 6 reinforced with glass fiber, with metric thread EN 60423.

On request: polystyrene lock nuts (-20°C / +70°C) in the three RAL colors (example for M12, gray RAL 7035: P-CT M1244.19), lock nuts up to M32 in polycarbonate (-40°C / +135°C) in the colors gray RAL 7035 and black RAL 9005 (example for M12, gray RAL 7035: P-CT M1224.19).

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	thread pitch	thread value	key mm	H mm	pack pcs.
P-CT M1006.14*	black RAL 9005	PA 6 (25% FV)	Metric	10x1.5	14	5	100
P-CT82 M1204.17	gray RAL 7035	PA 6 (30% FV)	Metric	12x1.5	17	5	100
P-CT82 M1206.17	black RAL 9005	PA 6 (30% FV)	Metric	12x1.5	17	5	100
P-CT M1204.19	gray RAL 7035	PA 6 (25% FV)	Metric	12x1.5	19	5	50
P-CT M1205.19	gray RAL 7001	PA 6 (25% FV)	Metric	12x1.5	19	5	50
P-CT M1206.19	black RAL 9005	PA 6 (25% FV)	Metric	12x1.5	19	5	50
P-CT M1604.22	gray RAL 7035	PA 6 (25% FV)	Metric	16x1.5	22	5	50
P-CT M1605.22	gray RAL 7001	PA 6 (25% FV)	Metric	16x1.5	22	5	50
P-CT M1606.22	black RAL 9005	PA 6 (25% FV)	Metric	16x1.5	22	5	50
P-CT82 M1604.22	gray RAL 7035	PA 6 (30% FV)	Metric	16x1.5	22	5	100
P-CT82 M1606.22	black RAL 9005	PA 6 (30% FV)	Metric	16x1.5	22	5	100
P-CT M2004.24	gray RAL 7035	PA 6 (25% FV)	Metric	20x1.5	24	5	50
P-CT M2005.24	gray RAL 7001	PA 6 (25% FV)	Metric	20x1.5	24	5	50
P-CT M2006.24	black RAL 9005	PA 6 (25% FV)	Metric	20x1.5	24	5	50
P-CT82 M2004.26	gray RAL 7035	PA 6 (30% FV)	Metric	20x1.5	26	6	100
P-CT82 M2006.26	black RAL 9005	PA 6 (30% FV)	Metric	20x1.5	26	6	100
P-CT M2504.30	gray RAL 7035	PA 6 (25% FV)	Metric	25x1.5	30	6	20
P-CT M2505.30	gray RAL 7001	PA 6 (25% FV)	Metric	25x1.5	30	6	20
P-CT M2506.30	black RAL 9005	PA 6 (25% FV)	Metric	25x1.5	30	6	20
P-CT82 M2504.32	gray RAL 7035	PA 6 (30% FV)	Metric	25x1.5	32	6	100
P-CT82 M2506.32	black RAL 9005	PA 6 (30% FV)	Metric	25x1.5	32	6	100
P-CT M3204.38	gray RAL 7035	PA 6 (25% FV)	Metric	32x1.5	38	7,5	20
P-CT M3205.38	gray RAL 7001	PA 6 (25% FV)	Metric	32x1.5	38	7,5	20
P-CT M3206.38	black RAL 9005	PA 6 (25% FV)	Metric	32x1.5	38	7,5	20
P-CT82 M3204.41	gray RAL 7035	PA 6 (30% FV)	Metric	32x1.5	41	7	100
P-CT82 M3206.41	black RAL 9005	PA 6 (30% FV)	Metric	32x1.5	41	7	100
P-CT82 M4004.50	gray RAL 7035	PA 6 (30% FV)	Metric	40x1.5	50	7	50
P-CT82 M4006.50	black RAL 9005	PA 6 (30% FV)	Metric	40x1.5	50	7	50
P-CT M4004.50	gray RAL 7035	PA 6 (25% FV)	Metric	40x1.5	50	8	20
P-CT M4005.50	gray RAL 7001	PA 6 (25% FV)	Metric	40x1.5	50	8	20

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





P-CT M4006.50	black RAL 9005	PA 6 (25% FV)	Metric	40x1.5	50	8	20
P-CT82 M5004.60	gray RAL 7035	PA 6 (30% FV)	Metric	50x1.5	60	8	50
P-CT82 M5006.60	black RAL 9005	PA 6 (30% FV)	Metric	50x1.5	60	8	50
P-CT M5004.60	gray RAL 7035	PA 6 (25% FV)	Metric	50x1.5	60	9	10
P-CT M5005.60	gray RAL 7001	PA 6 (25% FV)	Metric	50x1.5	60	9	10
P-CT M5006.60	black RAL 9005	PA 6 (25% FV)	Metric	50x1.5	60	9	10
P-CT82 M6304.75	gray RAL 7035	PA 6 (30% FV)	Metric	63x1.5	75	8	50
P-CT82 M6306.75	black RAL 9005	PA 6 (30% FV)	Metric	63x1.5	75	8	50
P-CT M6304.75	gray RAL 7035	PA 6 (25% FV)	Metric	63x1.5	75	10	10
P-CT M6305.75	gray RAL 7001	PA 6 (25% FV)	Metric	63x1.5	75	10	10
P-CT M6306.75	black RAL 9005	PA 6 (25% FV)	Metric	63x1.5	75	10	10

* article in polyamide reinforced with glass fiber and with operating temperature -40°C / +100°C.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

