



PLASTIC HEX LOCK NUTS (PG THREAD)

ITEM: P-CT82 PG3604.60

Codice EZ: request the code from our sales office

Material: polyamide 6 (PA 6) reinforced with glass fiber at 25% for P-CT or 30% for P-CT82.

Color: light gray Ral 7035, dark gray Ral 7001, black Ral 9005.

Use temperature: -30°C / +120°C

Flammability: flame retardant UL94-HB (P-CT)

Features: universal hexagonal lock nut in polyamide 6 reinforced with glass fiber, with PG thread DIN 40430/46320.

On request: polystyrene lock nuts (-20°C / +70°C) in the three RAL colors (example for P-CT in PG7, gray RAL 7035: P-CT PG744.15; example for P-CT82 in PG7, gray RAL 7035: P-CT82 PG744.19), polycarbonate locknuts (-40°C / +135°C) in gray RAL 7035 and black RAL 9005 (example for P-CT in PG7, gray RAL 7035: P-CT PG724.15 ; example for P-CT82 in PG7, gray RAL 7035: P-CT82 PG724.19).

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	Material	thread pitch	thread value	key mm	H mm	pack pcs.
P-CT82 PG3604.60	gray RAL 7035	PA 6 (30% FV)	PG	36	60	8	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

