



## CYLINDRICAL PLASTIC REDUCERS WITH HEXAGON (PG THREAD)

Material: polyamide 6 (PA 6) reinforced with glass fiber (30%), polycarbonate (PC).

Color: light gray RAL 7035, black RAL 9005.

Use temperature: -40°C / +100°C (PA 6), -40°C / +135°C (PC)

Features: cylindrical reductions with hexagonal base, available in both polyamide 6 and polycarbonate, used to allow the assembly of a cable gland in a hole with a diameter greater than that of the cable gland thread.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                 | Color          | Material | thread pitch 1 | thread value 1 | thread pitch 2 | thread value 2 | key mm | H1 mm | H2 mm | H3 mm | pack pcs. |
|----------------------|----------------|----------|----------------|----------------|----------------|----------------|--------|-------|-------|-------|-----------|
| P-REC PG904-PG 704   | gray RAL 7035  | PA 6     | PG             | 9              | PG             | 7              | 19     | 12,5  | 8     | -     | 100       |
| P-REC PG906-PG 706   | black RAL 9005 | PA 6     | PG             | 9              | PG             | 7              | 19     | 12,5  | 8     | -     | 100       |
| P-REC PG924-PG 724   | gray RAL 7035  | PC       | PG             | 9              | PG             | 7              | 19     | 8     | 7     | 7     | 50        |
| P-REC PG1104-P G904  | gray RAL 7035  | PA 6     | PG             | 11             | PG             | 9              | 22     | 14    | 8     | -     | 100       |
| P-REC PG1106-P G906  | black RAL 9005 | PA 6     | PG             | 11             | PG             | 9              | 22     | 14    | 8     | -     | 100       |
| P-REC PG1124-P G924  | gray RAL 7035  | PC       | PG             | 11             | PG             | 9              | 22     | 9     | 8     | 8     | 50        |
| P-REC PG1304-P G1104 | gray RAL 7035  | PA 6     | PG             | 13,5           | PG             | 11             | 24     | 15    | 9     | -     | 100       |
| P-REC PG1306-P G1106 | black RAL 9005 | PA 6     | PG             | 13,5           | PG             | 11             | 24     | 15    | 9     | -     | 100       |
| P-REC PG1324-P G1124 | gray RAL 7035  | PC       | PG             | 13,5           | PG             | 11             | 24     | 13    | 9     | 10    | 50        |
| P-REC PG1604-P G1304 | gray RAL 7035  | PA 6     | PG             | 16             | PG             | 13,5           | 27     | 17    | 10    | -     | 100       |

### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)  
Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993



|                            |                   |      |    |    |    |      |    |    |      |    |     |
|----------------------------|-------------------|------|----|----|----|------|----|----|------|----|-----|
| P-REC<br>PG1606-P<br>G1306 | black RAL<br>9005 | PA 6 | PG | 16 | PG | 13,5 | 27 | 17 | 10   | -  | 100 |
| P-REC<br>PG1624-P<br>G1324 | gray RAL<br>7035  | PC   | PG | 16 | PG | 13,5 | 27 | 12 | 9    | 10 | 50  |
| P-REC<br>PG4824-P<br>G4224 | gray RAL<br>7035  | PC   | PG | 48 | PG | 42   | 60 | 26 | 15,5 | 17 | 5   |

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

