



fig. A



fig. B



fig. C

METAL THREADED PLUGS WITH MEMBRANE FOR PRESSURE BALANCING - "EZ" SERIES (METRIC THREAD)

Material: caps in aluminum or stainless steel (DIN EN 1.4305 / AISI 303), oleophobic / hydrophobic membrane in acrylic copolymer, O-Ring in NBR.

Use temperature: -20°C / +100°C (with peaks of -30°C / +150°C)


IP protection: IP 67 / IP 68 (water penetration pressure = 0.1 / 1.45 bar / psi).

Features: caps characterized by micro-openings to allow ventilation and heat dissipation. They are internally equipped with a special oleophobic / hydrophobic membrane resistant to bases and many organic chemical agents; it guarantees an effective pressure balance, prevents the formation of humidity and condensation and limits the unwanted temperature increase inside the equipment on which these plugs are mounted. Consequently, the equipment is better protected from the risk of corrosion and thus its duration is extended. As you can see in the table, there are 3 types of caps which differ in material, shape and size; the BD-MTC cap is equipped with a flat section O-Ring gasket and is supplied complete with lock nut. The air flow is measured with a differential pressure of 70 mbar / 1 psi. Some of these plugs are UL classified for applications type 1, 4, 4X (according to UL50E). Complete with O-Ring. With metric thread - EN 60423.

On request: the steel plugs can be produced in stainless steel DIN EN 1.4404/AISI 316L.

Regulations and Certifications: c-UR-us (see table).

ATTENZIONE: DISEGNO RAPPRESENTATIVO.
PER OGNI ARTICOLO USARE IL PULSANTE "LENTE".



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Material	specific	thread pitch	thread value	air flow l/h	water penetration pressure bar/psi	H1 mm	H2 mm	ØB mm	key mm	pack pcs.
BD-MTA M4AL-4.3	aluminum	fig. TO	Metric	4x0.7	4	0,9/13	2,7	3	12,3	-	50
BD-MTA M4AL-7.3	aluminum	fig. TO	Metric	4x0.7	7	0,5/7,25	2,7	3	12,3	-	50
BD-MTA M4AL-35.3	aluminum	fig. TO	Metric	4x0.7	35	0,2/2,9	2,7	3	12,3	-	50
BD-MTA M4AL-100.3	aluminum	fig. TO	Metric	4x0.7	100	0,1/1,45	2,7	3	12,3	-	50
BD-MTA M8AL-4.8	aluminum	fig. TO	Metric	8x0.75	4	0,9/13	2,7	8	12,3	-	50
BD-MTA M8AL-7.8	aluminum	fig. TO	Metric	8x0.75	7	0,5/7,25	2,7	8	12,3	-	50
BD-MTA M8AL-35.8	aluminum	fig. TO	Metric	8x0.75	35	0,2/2,9	2,7	8	12,3	-	50

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





BD-MTA M8AL-100. 8	aluminum	fig. TO	Metric	8x0.75	100	0,1/1,45	2,7	8	12,3	-	50
BD-MTB M12X1AI-1 6.10	stainless steel	fig. B.	Metric	12x1	16	0,9/13	11	10	18,8	17	50
BD-MTB M12X1AI-2 5.10	stainless steel	fig. B.	Metric	12x1	25	0,5/7,25	11	10	18,8	17	50
BD-MTB M12X1AI-1 20.10	stainless steel	fig. B.	Metric	12x1	120	0,2/2,9	11	10	18,8	17	50
BD-MTB M12X1AI-3 00.10	stainless steel	fig. B.	Metric	12x1	300	0,1/1,45	11	10	18,8	17	50
BD-MTB M12AI-16.6 *	stainless steel	fig. B.	Metric	12x1.5	16	0,9/13	11	6	18,8	17	50
BD-MTB M12AI-16.1 0*	stainless steel	fig. B.	Metric	12x1.5	16	0,9/13	11	10	18,8	17	50
BD-MTB M12AI-25.6 *	stainless steel	fig. B.	Metric	12x1.5	25	0,5/7,25	11	6	18,8	17	50
BD-MTB M12AI-25.1 0*	stainless steel	fig. B.	Metric	12x1.5	25	0,5/7,25	11	10	18,8	17	50
BD-MTB M12AI-120. 6*	stainless steel	fig. B.	Metric	12x1.5	120	0,2/2,9	11	6	18,8	17	50
BD-MTB M12AI-120. 10*	stainless steel	fig. B.	Metric	12x1.5	120	0,2/2,9	11	10	18,8	17	50
BD-MTB M12AI-300. 6*	stainless steel	fig. B.	Metric	12x1.5	300	0,1/1,45	11	6	18,8	17	50
BD-MTB M12AI-300. 10*	stainless steel	fig. B.	Metric	12x1.5	300	0,1/1,45	11	10	18,8	17	50
BD-MTB M16AI-16.6 .12	stainless steel	fig. B.	Metric	16x1.5	16	0,9/13	12	6	20	18	50
BD-MTB M16AI-16.6 .16	stainless steel	fig. B.	Metric	16x1.5	16	0,9/13	16	6	20	18	50
BD-MTB M16AI-25.6 .12	stainless steel	fig. B.	Metric	16x1.5	25	0,5/7,25	12	6	20	18	50

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





BD-MTB M16AI-25.6 .16	stainless steel	fig. B.	Metric	16x1.5	25	0,5/7,25	16	6	20	18	50
BD-MTB M16AI-120. 6.12	stainless steel	fig. B.	Metric	16x1.5	120	0,2/2,9	12	6	20	18	50
BD-MTB M16AI-120. 6.16	stainless steel	fig. B.	Metric	16x1.5	120	0,2/2,9	16	6	20	18	50
BD-MTB M16AI-300. 6.12	stainless steel	fig. B.	Metric	16x1.5	300	0,1/1,45	12	6	20	18	50
BD-MTB M16AI-300. 6.16	stainless steel	fig. B.	Metric	16x1.5	300	0,1/1,45	16	6	20	18	50
BD-MTB M20AI-16.6 .13	stainless steel	fig. B.	Metric	20x1.5	16	0,9/13	13	6	24,5	22	50
BD-MTB M20AI-16.6 .17	stainless steel	fig. B.	Metric	20x1.5	16	0,9/13	17	6	24,5	22	50
BD-MTB M20AI-25.6 .13	stainless steel	fig. B.	Metric	20x1.5	25	0,5/7,25	13	6	24,5	22	50
BD-MTB M20AI-25.6 .17	stainless steel	fig. B.	Metric	20x1.5	25	0,5/7,25	17	6	24,5	22	50
BD-MTB M20AI-120. 6.13	stainless steel	fig. B.	Metric	20x1.5	120	0,2/2,9	13	6	24,5	22	50
BD-MTB M20AI-120. 6.17	stainless steel	fig. B.	Metric	20x1.5	120	0,2/2,9	17	6	24,5	22	50
BD-MTB M20AI-300. 6.13	stainless steel	fig. B.	Metric	20x1.5	300	0,1/1,45	13	6	24,5	22	50
BD-MTB M20AI-300. 6.17	stainless steel	fig. B.	Metric	20x1.5	300	0,1/1,45	17	6	24,5	22	50
BD-MTC M40AI-120. 10*	stainless steel	fig. C.	Metric	40x1.5	120	0,9/13	20,5	10	58	-	1
BD-MTC M40AI-375. 10*	stainless steel	fig. C.	Metric	40x1.5	375	0,5/7,25	20,5	10	58	-	1
BD-MTC M40AI-135 0.10*	stainless steel	fig. C.	Metric	40x1.5	1350	0,2/2,9	20,5	10	58	-	1

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





BD-MTC	stainless	fig. C.	Metric	40x1.5	2200	0,1/1,45	20,5	10	58	-	1
M40AI-220	steel										
0.10*											

* C-UR-us, UL type 1, 4, 4X certified item.

NB: THE TECHNICAL DRAWING NEXT TO THE IMAGE IS REPRESENTATIVE. TO VIEW THE TECHNICAL DRAWING OF A SINGLE ITEM, CLICK ON THE LENS BUTTON.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

