




METAL THREADED PLUGS WITH O-RING (GAS THREAD)

Material: nickel-plated brass cap, 70 Sh A nitrile O-Ring.

Use temperature: -25°C / +120°C

IP protection: IP 68.

Features: screwdriver slotted threaded caps, complete with O-Ring.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	ØB mm	H1 mm	H2 mm	pack pcs.
TFC OR G38.17	GAS	3/8"	17	3	6	50
TFC OR G38.17 L	GAS	3/8"	17	3	14,5	50
TFC OR G12.22	GAS	1/2"	22	3	6,5	50
TFC OR G12.22 L	GAS	1/2"	22	3	14,5	50
TFC OR G58.24	GAS	5/8"	24	3	6,5	50
TFC OR G58.24 L	GAS	5/8"	24	3	14,5	50
TFC OR G34.28	GAS	3/4"	28	3	7	20
TFC OR G34.28 L	GAS	3/4"	28	3	14,5	20
TFC OR G1.35	GAS	1"	35	4	8	20
TFC OR G1.35 L	GAS	1"	35	4	14,5	20
TFC OR G114.44	GAS	1" 1/4	44	4,5	8,5	20
TFC OR G114.44 L	GAS	1" 1/4	44	4,5	15	20
TFC OR G112.50	GAS	1" 1/2	50	6	9	10
TFC OR G112.50 L	GAS	1" 1/2	50	6	15	10
TFC OR G2.64	GAS	2"	64	6	10	5
TFC OR G2.64 L	GAS	2"	64	6	15	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

