




METAL THREADED CAPS WITH O-RING (PG THREAD)

Material: nickel-plated brass cap, 70 Sh A nitrile O-Ring.

Use temperature: -25°C / +120°C

IP protection: IP 68.

Features: screwdriver slotted threaded caps, complete with O-Ring.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	thread pitch	thread value	ØB mm	H1 mm	H2 mm	pack pcs.
TFC OR PG7.14	PG	7	14	3	5	50
TFC OR PG7.14 L	PG	7	14	3	12	50
TFC OR PG9.17	PG	9	17	3	6	50
TFC OR PG9.17 L	PG	9	17	3	12	50
TFC OR PG11.20	PG	11	20	3	6	50
TFC OR PG11.20 L	PG	11	20	3	12	50
TFC OR PG13.22	PG	13,5	22	3	6,5	50
TFC OR PG13.22 L*	PG	13,5	22	3	10	50
TFC OR PG16.24	PG	16	24	3	6,5	50
TFC OR PG16.24 L	PG	16	24	3	12	50
TFC OR PG21.30	PG	21	30	4	7	20
TFC OR PG21.30 L	PG	21	30	4	12	20
TFC OR PG29.39	PG	29	39	4	8	20
TFC OR PG29.39 L	PG	29	39	4	12	20
TFC OR PG36.50	PG	36	50	6	9	10
TFC OR PG36.50 L	PG	36	50	6	15	10
TFC OR PG42.57	PG	42	57	6	10	5
TFC OR PG42.57 L	PG	42	57	6	15	5
TFC OR PG48.64	PG	48	64	6	10	5
TFC OR PG48.64 L	PG	48	64	6	15	5

* Item with NBR O-Ring and operating temperature -40°C / +100°C.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

