



PRESSURE PLUGS IN POLYAMIDE PERFORATED WITH MEMBRANE FOR BALANCING THE PRESSURE - "HEYCO" SERIES

Material: polyamide 6/6 plugs, oleophobic/hydrophobic acrylic copolymer membrane, integrated O-Ring under the head.

Color: black.


Use temperature: -40°C / +105°C

IP protection: IP 65 / IP 67 / IP 68.

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these particular caps are perforated (holes with Ø 2.4 mm) to allow ventilation and heat dissipation. They are characterized by the special internal membrane which guarantees both an effective pressure balance and a continuous air exchange and which prevents the formation of humidity and the intrusion of liquids inside the equipment on which they are mounted. The membrane is firmly fixed inside the cap by means of ultrasonic welding. These plugs are UL classified for NEMA 3R, 4 and 4X type applications. Thanks to the fixing teeth, they snap into place and adapt to the thickness of the frame up to the maximum indicated in the table. Air flow is measured across an area of 3.7 cm² with an average pressure of 930 mbar/13.5 psi. On request: for quantity, they can be supplied in gray or in other colors.

Regulations and Certifications: c-UR-us.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	air flow l/h	H mm	ØG mm	G1 mm	max frame thickness mm	pack pcs.
LTSV 500 NERI	1000	15,2	12,7	11,4	3,2	100
LTSV 875 NERI	1000	15,7	22,2	19,6	3,2	100
LTSV 1125 NERI	1000	16,8	28,6	25,4	3,2	100

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

