



PLUGS IN POLYAMIDE WITH MEMBRANE FOR BALANCING THE PRESSURE - SERIES "EZ"

Material: caps in polyamide 6, oleophobic/hydrophobic membrane in acrylic copolymer, O-Ring in NBR.

Color: light gray Ral 7035, dark gray Ral 7001, black Ral 9005.

Use temperature: -40°C / +100°C (with peaks of -45°C / +150°C)

IP protection: IP 67 / IP 68 (pressione di penetrazione dell'acqua = 0,1/1,45 bar/psi).

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: snap-fit caps characterized by lateral micro-holes to allow ventilation and heat dissipation. They are internally equipped with a special oleophobic/hydrophobic membrane resistant to bases and to many organic chemical agents; it guarantees an effective pressure balance, prevents the formation of humidity and condensation and limits the unwanted temperature increase inside the equipment on which these plugs are mounted. Consequently, the equipment is better protected from the risk of corrosion and thus its duration is extended. As you can see in the table, there are 2 types of caps which differ in shape and size. The air flow is measured with a differential pressure of 70 mbar/1 psi. Complete with flat section O-Ring gasket. We suggest making a mounting hole as per our instructions in order not to deform the coupling and to obtain IP 67/68 protection.



fig. A

fig. B





fig. A

fig. B



FORO DI MONTAGGIO

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	specific	Ø mounting hole mm	air flow l/h	water penetration n pressure bar/psi	H1 mm	H2 mm	ØB mm	frame thickness mm	key mm	pack pcs.
BD-INA 6,4.04-15.3 ,2	gray RAL 7035	fig. TO	6,4	15	0,5/7,25	7,8	5,9	15	3,2	12	500
BD-INA 6,4.05-15.3 ,2	gray RAL 7001	fig. TO	6,4	15	0,5/7,25	7,8	5,9	15	3,2	12	500
BD-INA 6,4.06-15.3 ,2	black RAL 9005	fig. TO	6,4	15	0,5/7,25	7,8	5,9	15	3,2	12	500
BD-INB 6,4.04-16.3 ,2	gray RAL 7035	fig. B.	6,4	16	0,9/13	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.05-16.3 ,2	gray RAL 7001	fig. B.	6,4	16	0,9/13	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.06-16.3 ,2	black RAL 9005	fig. B.	6,4	16	0,9/13	10,9	5,9	18,5	3,2	-	500

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993



BD-INA 6,4.04-25.3 ,2	gray RAL 7035	fig. TO	6,4	25	0,5/7,25	7,8	5,9	18,5	3,2	17	500
BD-INA 6,4.05-25.3 ,2	gray RAL 7001	fig. TO	6,4	25	0,5/7,25	7,8	5,9	18,5	3,2	17	500
BD-INA 6,4.06-25.3 ,2	black RAL 9005	fig. TO	6,4	25	0,5/7,25	7,8	5,9	18,5	3,2	17	500
BD-INA-P 6,4.04-25.3 ,2*	gray RAL 7035	fig. TO	6,4	25	0,2/2,9	7,8	5,9	18,5	3,2	12	500
BD-INA-P 6,4.05-25.3 ,2*	gray RAL 7001	fig. TO	6,4	25	0,2/2,9	7,8	5,9	18,5	3,2	12	500
BD-INA-P 6,4.06-25.3 ,2*	black RAL 9005	fig. TO	6,4	25	0,2/2,9	7,8	5,9	18,5	3,2	12	500
BD-INB 6,4.04-25.3 ,2	gray RAL 7035	fig. B.	6,4	25	0,5/7,25	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.05-25.3 ,2	gray RAL 7001	fig. B.	6,4	25	0,5/7,25	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.06-25.3 ,2	black RAL 9005	fig. B.	6,4	25	0,5/7,25	10,9	5,9	18,5	3,2	-	500
BD-INA-P 6,4.04-50.3 ,2*	gray RAL 7035	fig. TO	6,4	50	0,2/2,9	7,8	5,9	18,5	3,2	17	500
BD-INA-P 6,4.05-50.3 ,2*	gray RAL 7001	fig. TO	6,4	50	0,2/2,9	7,8	5,9	18,5	3,2	17	500
BD-INA-P 6,4.06-50.3 ,2*	black RAL 9005	fig. TO	6,4	50	0,2/2,9	7,8	5,9	18,5	3,2	17	500
BD-INB 6,4.04-120. 3,2	gray RAL 7035	fig. B.	6,4	120	0,2/2,9	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.05-120. 3,2	gray RAL 7001	fig. B.	6,4	120	0,2/2,9	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.06-120. 3,2	black RAL 9005	fig. B.	6,4	120	0,2/2,9	10,9	5,9	18,5	3,2	-	500
BD-INB 6,4.04-300. 3,2	gray RAL 7035	fig. B.	6,4	300	0,1/1,45	10,9	5,9	18,5	3,2	-	500

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





BD-INB	gray RAL	fig. B.	6,4	300	0,1/1,45	10,9	5,9	18,5	3,2	-	500
6,4.05-300.	7001										
3,2											

BD-INB	black RAL	fig. B.	6,4	300	0,1/1,45	10,9	5,9	18,5	3,2	-	500
6,4.06-300.	9005										
3,2											

* Item with PTFE membrane, which is highly resistant to chemicals and is resistant to high temperatures (up to +260°C).

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

