



TAPPI IN POLIAMMIDE AUTOESTINGUENTI E SENZA ALOGENI - SERIE "HEYCO" -

Material: polyamide 6/6.


Color: black.

Use temperature: max +105°C

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: these caps have good chemical resistance and good electrical properties.

They have a convex head and are produced in a polyamide treated in such a way that, in the event of a fire, it does not burn and does not produce toxic gases. They contain neither halogens nor phosphorus and are very resistant to UV rays. Thanks to the fastening teeth, these caps snap on and adapt to the thickness of the frame up to a maximum indicated in the table.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Ø mounting hole mm	max frame thickness mm	ØB mm	H mm	pack pcs.
HFP-187	4,7	1,6	6,4	6,1	500
HFP-250	6,4	1,6	7,9	7,9	500
HFP-312	7,9	1,6	9,5	7,9	500
HFP-375	9,5	3,2	11,9	10,3	500
HFP-437	11,1	3,2	13,5	10,3	500
HFP-500	12,7	3,2	14,7	10,3	500
HFP-625	15,9	3,2	18,2	10,3	500
HFP-750	19,1	3,2	23,4	10,3	500
HFP-875	22,2	3,2	25,8	11,5	500
HFP-1000	25,4	3,2	30,6	11,5	200
HFP-1093	27,8 - 28,6	3,2	30,9	11,5	200
HFP-1250	31,7	3,2	34,9	11,5	200
HFP-1375	34,9	3,2	38,1	11,5	200
HFP-1500	38,1	3,2	42,4	11,5	200
HFP-1750	44,5	3,2	48,7	11,5	200
HFP-2000	50,8	3,2	55,1	11,9	200

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

