



TAPPI IN TPE A TENUTA IP 66 - SERIE "HEYCO"

Material: santoprene (thermoplastic rubber), hardness: 85 Sh A.

Color: black.


Use temperature: -60°C / +135°C

IP protection: IP 66, Nema 4 e 4X.

Flammability: flame retardant and self-extinguishing UL94-V0.

Features: these caps have a convex head and are resistant to oil and rain. They are UL certified for outdoor use. Certified for NEMA 4 and 4X applications. They are fixed by pressure.

Regulations and Certifications: UL, UR, CSA.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Ø mounting hole mm	spessore telaio min - max mm	ØB mm	H mm	H1 mm	pack pcs.
KOS-LT 500*	12,7	0,8 - 3,2	23,1	11,4	7,4	250
KOS-LT 625*	15,9	0,8 - 3,2	26,2	11,9	7,9	250
KOS-LT 750*	19,1	0,8 - 3,2	29,2	13	8,9	250
KOS-LT 1/2**	22,2	0,8 - 3,2	32,5	13,5	9,1	100
KOS-LT 1/2 LD***	22,2	0,8 - 3,2	32,5	13,5	9,1	-
KOS-LT 1000*	25,4	0,8 - 3,2	35,8	14,2	10,2	100
KOS-LT 3/4**	27,8	0,8 - 3,2	38,6	14	10,2	50
KOS-LT 3/4 LD***	27,8	0,8 - 3,2	38,6	14	10,2	-
KOS-LT 1**	34,9	0,8 - 3,2	45,2	14,5	10,7	50
KOS-LT 1 LD***	34,9	0,8 - 3,2	45,2	14,3	10,7	-

*Articolo a normativa UR. **Articolo a normativa UL. ***Articolo in TPE più morbido con durezza 75 Sh A, a normativa UL. Per quantità, può essere fornito in colore grigio.

THE ITEMS FOR WHICH THE QUANTITY PER PACKAGE IS NOT SPECIFIED ARE ON REQUEST AND SUBJECT TO A MINIMUM QUANTITY AVAILABLE TO BE REQUESTED AT OUR SALES OFFICE.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

