



PERFORATED POLYAMIDE PLUGS - "HEYCO" SERIES -

Material: polyamide 6/6.

Color: black.


Use temperature: -40°C / +105°C

Flammability: flame retardant and self-extinguishing UL94-V2.

Features: these caps have a convex head and are perforated to allow ventilation and heat dissipation. The caps from VP-500 to VP-875 have the holes with Ø 2.4 mm, while the remaining caps have the holes with Ø 3.2 mm. The thickness of the head is almost always about 1.6 mm. Thanks to the fastening teeth, these caps snap on and adapt to the thickness of the frame up to a maximum indicated in the table.

On request: for quantity, they can be supplied in white or in other colors also on sample.

Regulations and Certifications: UR, CSA.



The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	specific	Ø mounting hole mm	max frame thickness mm	ØB mm	H mm	n. holes	pack pcs.
VP-500	-	12,7	3,2	14,7	10,3	4	500
VPT-500	for thick frames	12,7	6,4	14,7	14,3	4	500
VP-562	-	14,3	3,2	16,7	10,3	4	500
VP-625	-	15,9	3,2	18,7	10,3	5	500
VPT-625	for thick frames	15,9	6,4	18,7	14,3	5	500
VP-750	-	19,1	3,2	23	10,3	8	500
VPT-750	for thick frames	19,1	6,4	23	14,3	8	500
VP-812	-	20,6	3,2	22,6	11,5	8	500
VP-875	-	22,2	3,2	25,8	11,5	9	500
VPT-875	for thick frames	22,2	6,4	25,8	14,3	9	500
VP-1000	-	25,4	3,2	30,6	11,5	9	200
VPT-1000	for thick frames	25,4	6,4	30,6	14,3	9	500
VP-1093	-	27,8 - 28,6	3,2	30,9	11,5	9	200
VPT-1093	for thick frames	27,8 - 28,6	6,4	30,9	14,3	9	500
VP-1187	-	30,1	3,2	33,3	11,5	10	200
VPT-1187	for thick frames	30,1	6,4	33,3	14,3	10	200
VP-1250	-	31,7	3,2	34,9	11,5	10	100
SVP-1250-4	-	31,7	3,2	34,9	11,5	4	100
VPT-1250	for thick frames	31,7	6,4	34,9	14,3	10	200
VP-1375	-	34,9	3,2	38,1	11,5	11	100
VPT-1375	for thick frames	34,9	6,4	38,1	14,3	11	200
VP-1500	-	38,1	3,2	42,4	11,5	13	100
VPT-1500	for thick frames	38,1	6,4	42,4	14,3	13	200
VP-1750	-	44,5	3,2	48,4	11,5	13	100
VPT-1750	for thick frames	44,5	6,4	48,4	14,3	13	200
VP-2000	-	50,8	3,2	54,4	11,9	19	100
VPT-2000	for thick frames	50,8	6,4	54,4	14,7	19	200

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993



VP-2.5	-	63,5	6,4	69	19,1	19	50
VP-3.0	-	76,2	6,4	80	18,8	26	50
VP-3.5	-	88,9	6,4	92,9	19,1	38	50
VP-4.0	-	101,6	6,4	105,6	19,1	48	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

