



## PLASTIC FLANGED HOSE BRACKETS (METRIC THREAD)

### ITEM: RQF2-M 25 GRIGIO

**Codice EZ: 157511, PLASTIC Flexa code: 15020071025.**

Material: polyamide.

Color: gray or black.

Use temperature: -40°C / +120°C

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: NFPA 130.

Features: these brackets make it possible to transform fittings with metric thread into flanged fittings to be then used where a threaded hole is not available or a lock nut cannot be used. They are provided with holes for fixing to the wall by means of screws; from article RQF2-M 40 onwards they have 4 holes. To ensure that the 45°/90° fittings, screwed inside, can be positioned in the desired direction, it is advisable to mount a flat section O-ring gasket at the base of the thread of the fittings themselves. To ensure watertightness, it is advisable to mount a round section O-ring gasket on the edge of the flanged hole. The black brackets are UV resistant.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	thread pitch	thread value	ØB1 mm	L mm	L1 mm	H mm	H1 mm	And mm	pack pcs.
RQF2-M 25 GRIGIO	Grey	Metric	M 25x1.5	29,5	46	36	32	—	15,5	50

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

