



"DUO" CORRUGATED PIPE IN POLYPROPYLENE (UL94-V2)

Material: polypropylene.

Color: black.

Use temperature: -25°C / +135°C (con punte fino a +150°C)

IP protection: IP 40.

Flammability: flame retardant and self-extinguishing UL94-V2.

Regulations and Certifications: UKCA.

Features: this particular tube actually consists of two separate tubes, one inside the other, both with side opening along the entire length; once assembled they are a single, closed tube. Thanks to the side openings, it can be installed on pre-wired cables or used in replacing damaged pipes. It is characterized by good flexural strength, good resistance to chemicals and UV rays and superior insulation properties thanks to the fact that the characteristics of the material do not depend on humidity. It does not contain cadmium or phosphorus. For correct assembly, use the specific "DUO" series accessories, ie the fittings "RQG-DUO-M" and the locknuts "GMK-DUO M". Application sectors: electrical systems (according to DIN EN 60204), plant engineering / on-board machines, post-assembly repairs.

Crushing resistance: 500 N

Impact resistance: -

Tensile strength: -

(Tests carried out with pipes in dimension AD21,2 according to the specifications DIN EN IEC 61386-23)

On request: it can be supplied in packages with smaller sizes.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	Ø int. x Ø est. mm	static bending radius mm (± 10%)	dynamic bending radius mm (± 10%)	pack mt.
PP-DUO AD10 NERO	10	5.6x10.3	30	90	50
PP-DUO AD13 NERO	13	8.5x13.3	40	120	50
PP-DUO AD15,8 NERO	15,8	11x16	50	150	50
PP-DUO AD21,2 NERO	21,2	15.1x21.3	65	200	50
PP-DUO AD25,4 NERO	25,4	19.6x25.4	75	230	50
PP-DUO AD28,5 NERO	28,5	21.6x28.1	80	240	50
PP-DUO AD31,5 NERO	31,5	24x31.5	100	300	25
PP-DUO AD34,5 NERO	34,5	26.8x34.4	110	330	25
PP-DUO AD42,5 NERO	42,5	31.8x42.7	145	440	25
PP-DUO AD54,5 NERO	54,5	43.9x53.9	150	450	25
PP-DUO AD79 NERO	79	60.5x78	220	660	10

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

