



HIGH TEMPERATURE CORRUGATED PIPE IN POLYAMIDE 6 (UL94-V2)

Material: modified polyamide 6.

Color: black.

Use temperature: -25°C / +150°C (with peaks up to +170°C)

IP protection: IP 68, IP 69.

Flammability: flame retardant and self-extinguishing UL94-V2.

Regulations and Certifications: VDE (EN/IEC 61386-23).

Features: good flexibility. Resistance to water, oils (max + 80 ° C), gasoline and in particular to acids and solvents. Excellent resistance to fuels, mineral oils, fats, alkalis, acids and bases. Good resistance to UV rays. It does not contain cadmium, silicone or halogens. Sectors of application: electrical systems (according to DIN EN 60204), plant engineering / machine board.

Compressive strength: 125 N

Impact resistance: 2 Kg

Tensile strength: 100 N

(Tests carried out with pipes in dimension AD21,2 according to the specifications DIN EN IEC 61386-23)

On request: with a surcharge on the price, the tube is available both in pieces and with side opening along the entire length.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	Ø int. x Ø est. mm	static bending radius mm (± 10%)	dynamic bending radius mm (± 10%)	pack mt.
PA 6-HT AD10 NERO	10	6.7x10	13	35	50
PA 6-HT AD13 NERO	13	9.7x12.9	20	45	50
PA 6-HT AD15,8 NERO	15,8	12.1x15.7	35	55	50
PA 6-HT AD21,2 NERO	21,2	16.4x21.3	45	75	50
PA 6-HT AD28,5 NERO	28,5	22.9x28.4	55	100	50
PA 6-HT AD34,5 NERO	34,5	28.8x34.4	65	120	25
PA 6-HT AD42,5 NERO	42,5	36.1x42.3	90	150	25
PA 6-HT AD54,5 NERO	54,5	47.8x54.3	100	190	25

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

