



"EASY-ENTRY" 45° PLASTIC FITTINGS WITH METAL THREAD IP 68/IP 69K (PG THREAD)

Material: body in polyamide 6, internal gasket in TPE, thread in nickel-plated brass.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102 , I3/F2), EN 45545-2 (HL 2), LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The rounded shape of the elbow facilitates the passage of cables ("EASY-ENTRY"). The metal thread gives the fittings maximum tightness when tightened whether they are mounted with the lock nut or mounted directly on the structure. The thread is internally coated in plastic to give maximum insulation to the cables. They are available with PG, Metric thread. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	K mm	J mm	key mm	pack pcs.
RQBK45-M 12 AD10 NERI	10	Metric	12x1.5	6,5	18	10	45	39	18	50
RQBK45-M 16 AD13 NERI	13	Metric	16x1.5	8,5	22	12	48	42,5	21	50
RQBK45-M 20 AD15,8 NERI	15,8	Metric	20x1.5	10	25,5	12	52,5	44,5	24	50
RQBK45-M 20 AD21,2 NERI	21,2	Metric	20x1.5	13	29,5	12	60	55	26	50
RQBK45-M 25 AD21,2 NERI	21,2	Metric	25x1.5	14,5	29,5	13	60	56	26	50
RQBK45-M 25 AD28,5 NERI	28,5	Metric	25x1.5	17	37	13	72	64	32	25

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQBK45-M 32 AD28,5 NERI	28,5	Metric	32x1.5	20	38	14	75	64	37	25
RQBK45-M 32 AD34,5 NERI	34,5	Metric	32x1.5	23	44	14	76	73,5	39	10
RQBK45-M 40 AD34,5 NERI	34,5	Metric	40x1.5	29	47	14	77	73,5	46	10
RQBK45-M 40 AD42,5 NERI	42,5	Metric	40x1.5	31,5	56,5	17	86	82,5	48	10
RQBK45-M 50 AD42,5 NERI	42,5	Metric	50x1.5	36	61,5	17	86	82,5	59	10
RQBK45-M 50 AD54,5 NERI	54,5	Metric	50x1.5	35,5	64	17	95	92	59	5
RQBK45-M 63 AD54,5 NERI	54,5	Metric	63x1.5	45,5	71,5	17	100	97	69	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

