


The drawing is indicative and the proportions may not

correspond to the table or real dimensions.







"EASY-ENTRY" 90° PLASTIC FITTINGS WITH ROTATING METAL THREAD IP 68/IP 69K (PG THREAD)

## ITEM: RQBK90DR-M 40 AD42,5 L17

Codice EZ: request the code from our sales office, "EASY-ENTRY" Flexa code: 15121042

Material: body in polyamide 6, internal gasket in TPE, thread in nickel-plated brass.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6). Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102, I3/F2), EN 45545-2 (HL 2).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance. They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The swiveling threaded head allows you to position the fittings in the desired direction even after installing them. The metal thread gives maximum tightness to tightening both in the case in which they are mounted with the lock nut and directly on the structure. The rounded shape of the elbow facilitates the passage of cables ("EASY-ENTRY"). They are available with PG, Metric and NPT threads. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	And mm	key mm	pack pcs.
RQBK90DR- M 40 AD42,5 L17	42,5	Metric	40x1.5	31,5	52	17	111	103	52	10
NERI										

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso





