



"EASY-ENTRY" 90° PLASTIC FITTINGS WITH ROTATING METAL THREAD IP 68/IP 69K (NPT THREAD)

Material: body in polyamide 6, internal gasket in TPE, thread in nickel-plated brass.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102 , I3/F2), EN 45545-2 (HL 2).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The swiveling threaded head allows you to position the fittings in the desired direction even after installing them. The metal thread gives maximum tightness to tightening both in the case in which they are mounted with the lock nut and directly on the structure. The rounded shape of the elbow facilitates the passage of cables ("EASY-ENTRY"). They are available with PG, Metric and NPT threads. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	And mm	key mm	pack pcs.
RQBK90DR-N 1/2 AD21,2 NERI*	21,2	NPT	1/2"	13	29,5	13	73	65	27	50
RQBK90DR-N 3/4 AD28,5 NERI*	28,5	NPT	3/4"	17	37	14	90	81,5	34	25
RQBK90DR-N 1 AD34,5 NERI*	34,5	NPT	1"	24,5	44	14	100	95	43	10
RQBK90DR-N 1 1/4 AD42,5 NERI*	42,5	NPT	1" 1/4	31,5	52	17	110	105	52	10

* Article on request.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

