



RACCORDI IN PLASTICA A 90° IP 66 (FILETTO NPT)

Material: polyamide 6.6.

Color: black.

Use temperature: -40°C / +120°C

IP protection: IP 66 according to EN 60529/IEC 60529 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: VDE (EN/IEC 61386-23), c-UR-us (file n.E86359, UL 1696 - CSA 22.2), LLOYD'S REGISTER, GOST.

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 66 sealing thanks to the conical structure of the interior. Resistance to oils, petrol and in particular to acids and solvents. They do not contain cadmium, silicone or halogens. With NPT thread according to ANSI/ASME B1.20.1.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	ØB1 mm	F mm	And mm	H1 mm	pack pcs.
RQW1-N 1/2 AD15,8 NERI	15,8	NPT	1/2"	16	26	26	11	40,5	42	50
RQW1-N 1/2 AD21,2 NERI	21,2	NPT	1/2"	16	29,5	27	13	48,5	51	50
RQW1-N 3/4 AD28,5 NERI	28,5	NPT	3/4"	21	37	34	14	57	57,5	25
RQW1-N 1 AD34,5 NERI	34,5	NPT	1"	28	44	43	16	66	67,5	10
RQW1-N 1 1/4 AD42,5 NERI	42,5	NPT	1" 1/4	35	52	52	18	76	83	10
RQW1-N 2 AD54,5 NERI	54,5	NPT	1" 1/2	41	64	64,5	18	87	95	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

