



90° PLASTIC FITTINGS IP 68 (NPT THREAD) ITEM: RQW-N 1/2 AD15,8 NERI

Codice EZ: 156623, 90° Flexa code: 15020057205.

Material: body in polyamide, internal gasket in TPE.

Color: black.

Use temperature: -40°C / +120°C

IP protection: IP 68, IP 69.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide).

Regulations and Certifications: VDE (EN / IEC 61386-23), TÜV VD / GGVSEB, EN 45545-2 HL2, DB, SNCF, NFPA 130 (ASTM E 162 / E 662, SMP 800-C), LLOYD'S REGISTER, c-UR-us (UL 1696 / CSA C22.2, file no.E86359), GOST.

Features: these fittings ensure excellent mechanical, tear-proof and anti-vibration resistance and guarantee IP 68 and IP 69 protection for maximum pressurized water tightness. The items indicated in the table comply with the requirements according to UL 514B (CSA C22.2 Nr. 18.3-12) and are specifically suitable to be assembled with the corrugated pipe PA 6-UL-SD so as to be able to create a "UL Listed" certified installation ". They are resistant to oils, petrol and in particular to acids and solvents. Good resistance to UV rays. They do not contain cadmium, silicone or halogens. With NPT thread - ANSI/ASME B1.20.1.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	ØB1 mm	F mm	And mm	H1 mm	pack pcs.
RQW-N 1/2 AD15,8 NERI	15,8	NPT	1/2"	14	23,5	26	12	40,5	42	50

* Item complies with the requirements according to UL 514B (CSA C22.2 Nr. 18.3-12).

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

