



90° PLASTIC FITTINGS IP 68 (PG THREAD)

Material: body in polyamide 6.6, internal gasket in TPE.

Color: gray, black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102 , I3/F2), EN 45545-2 (HL 2), TÜV VD/GGVSEB, LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K watertightness for maximum pressurized water tightness. They are available with PG, Metric, CTG (JIS B 0204)/Whitworth (DIN ISO 228-1), NPT threads. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	ØB1 mm	F mm	And mm	H1 mm	pack pcs.
RQW-P 7 AD10 GRIGI	Grey	10	PG	7	7	17	16	9,5	33	34	50
RQW-P 7 AD10 NERI	black	10	PG	7	7	17	16	9,5	33	34	50
RQW-P 9 AD13 GRIGI	Grey	13	PG	9	12	20	20	10	34	37	50
RQW-P 9 AD13 NERI	black	13	PG	9	12	20	20	10	34	37	50
RQW-P 11 AD13 GRIGI	Grey	13	PG	11	14	20	23	10	34	39	50
RQW-P 11 AD13 NERI	black	13	PG	11	14	20	23	10	34	39	50
RQW-P 13,5 AD13 NERI	black	13	PG	13,5	15,5	20	25	10	35	41	50
RQW-P 11 AD15,8 GRIGI	Grey	15,8	PG	11	14,5	24,5	24,5	10	37,5	42	50
RQW-P 11 AD15,8 NERI	black	15,8	PG	11	14,5	24,5	24,5	10	37,5	42	50

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQW-P 13,5 AD18,5 GRIGI	Grey	18,5	PG	13,5	13,5	26,5	27	13	47	46	50
RQW-P 13,5 AD18,5 NERI	black	18,5	PG	13,5	13,5	26,5	27	13	47	46	50
RQW-P 16 AD21,2 GRIGI	Grey	21,2	PG	16	18	29,5	27	13	48	49	50
RQW-P 16 AD21,2 NERI	black	21,2	PG	16	18	29,5	27	13	48	49	50
RQW-P 21 AD28,5 GRIGI	Grey	28,5	PG	21	24	37	34	13	58	57	25
RQW-P 21 AD28,5 NERI	black	28,5	PG	21	24	37	34	13	58	57	25
RQW-P 29 AD34,5 GRIGI	Grey	34,5	PG	29	32	44	43	15	65	67,5	10
RQW-P 29 AD34,5 NERI	black	34,5	PG	29	32	44	43	15	65	67,5	10
RQW-P 36 AD42,5 GRIGI	Grey	42,5	PG	36	39,5	52	51,5	15	72	83	10
RQW-P 36 AD42,5 NERI	black	42,5	PG	36	39,5	52	51,5	15	72	83	10
RQW-P 48 AD54,5 GRIGI	Grey	54,5	PG	48	48,5	64	65	16	84	96	5
RQW-P 48 AD54,5 NERI	black	54,5	PG	48	48,5	64	65	16	84	96	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

