



90° FLANGED PLASTIC FITTINGS IP 54 - "MULTI" SERIES

Material: polyamide 6.

Color: gray, black.

Use temperature: -40°C / +115°C

IP protection: IP 54 according to EN 60529 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: c-UR-us, UKCA.

Features: these fittings connect to the ROHRflex-MULTI hose much easier and faster than previous models. They ensure perfect mechanical, tear-proof and anti-vibration resistance. They comply with the EN 60204 standards for industrial machines and systems and allow the creation of protected and isolated installations. The flanged edge is provided with holes for fixing to the wall by means of screws. It is possible to increase the protection of these fittings from IP 54 to IP 65 or to IP 68 and IP 69K, by means of the gasket kit type MULTI-FRM. Each kit includes 2 gaskets: an internal flat and an external O-ring to be assembled on the flanged edge. They are very resistant to oils, petrol and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	tube size ID	ØB mm	And mm	L mm	L1 mm	L2 mm	H1 mm	H2 mm	H3 mm	H4 mm	pack pcs.
MULTI-W FP ID70 GRIGI	Grey	70	96,4	105	94	80,5	73	153	94	69	60,5	1
MULTI-W FP ID70 NERI	black	70	96,4	105	94	80,5	73	153	94	69	60,5	1
MULTI-W FP ID95 GRIGI	Grey	95	123	130	133,5	108	98,2	191	120	95	74	1
MULTI-W FP ID95 NERI	black	95	123	130	120	108	98,2	191	133,5	95	74	1

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

