



METAL FITTINGS IP 68 FOR BRAIDED CORRUGATED PIPES (METRIC THREAD)

Material: nickel-plated brass.

Color: silvered.

Use temperature: -40°C / +150°C

IP protection: IP 66, IP 68

Regulations and Certifications: CEI EN 61386-1, 61386-23, CEI EN 60423.

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance and high resistance to aggressive substances. The particular shape of the fitting allows double locking, both on the corrugated pipe and on the metal braid (on the entire circumference). The smooth inside of the fitting facilitates the passage of cables. Thanks to the internal gasket and the O-Ring on the external thread, these fittings guarantee IP 68 protection. Application sectors: plant engineering/machine board, railways.

On request: for quantity, they can be supplied with other types of threads, even female.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	ØA mm	B mm	F mm	H mm	wrench 1 mm	wrench 2 mm	wrench 3 mm	pack pcs.
RCDK-M 16 AD15,8	15,8	Metric	16x1.5	12	31	9	42	28	26	22	30
RCDK-M 20 AD21,2	21,2	Metric	20x1.5	15	39	10	61	35	30	28	20
RCDK-M 25 AD28,5	28,5	Metric	25x1.5	20	47	10	64	42	40	35	20
RCDK-M 32 AD34,5	34,5	Metric	32x1.5	27	56	13	71,5	50	50	42	10
RCDK-M 40 AD42,5	42,5	Metric	40x1.5	32	64	14	74	60	60	55	7
RCDK-M 50 AD54,5	54,5	Metric	50x1.5	44	76	18	86	70	70	65	5

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

