



IP 65 PLASTIC FITTINGS - "LIGHT" SERIES (PG THREAD)

ITEM: RQLG1-P 9 AD13 GRIGI

Codice EZ: request the code from our sales office, IP Flexa code: 15515013009.

Material: polyamide 6.

Color: gray, black.

Use temperature: -40°C / +120°C

IP protection: IP 65 according to EN 60529/IEC 60529 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: c-UR-us (file no. E86359).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 65 sealing thanks to the conical structure of the interior. The "LIGHT" series fittings are distinguished by the different design of the body. This does not contain inside the bush for the connection with the tube, but is equipped with locking teeth integrated into the body itself which perform the function of connection with the tube. To release it from the pipe, simply use a simple screwdriver with which the locking teeth are lifted and then the fitting can be reused. Resistance to oils, petrol and in particular to acids and solvents. They do not contain cadmium, silicone or halogens. With PG thread according to DIN 40430.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQLG1-P 9 AD13 GRIGI	Grey	13	PG	9	10	20	12	37	18	100

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

