



IP 66 PLASTIC FITTINGS (CTG THREAD)

Material: polyamide.

Color: black.

Use temperature: -40°C / +120°C

IP protection: IP 66.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: VDE (EN/IEC 61386-23), c-UR-us (file n. E86359, per le misure AD13-AD54,5), NFPA 130, LLOYD'S REGISTER, GOST.

Features: these fittings ensure excellent mechanical, tear-proof and anti-vibration resistance and guarantee IP 66 protection thanks to the conical internal structure.

They are resistant to oils, petrol and in particular to acids and solvents. Good resistance to UV rays. They do not contain cadmium, silicone or halogens. With CTG thread - JIS B 0204 / Whitworth - DIN ISO 228-1.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	filetto passo	filetto valore	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQG1-C 1/4 AD10 NERI	10	CTG	1/4"	7	17	10	32,5	16	50
RQG1-C 1/4 AD13 NERI	13	CTG	1/4"	9	20	10	35	18	50
RQG1-C 3/8 AD13 NERI	13	CTG	3/8"	10	21	10	35	18	50
RQG1-C 1/2 AD13 NERI	13	CTG	1/2"	13	27	14	39,5	18	50
RQG1-C 3/8 AD15,8 NERI	15,8	CTG	3/8"	12,5	23	10	37	21	50
RQG1-C 1/2 AD15,8 NERI	15,8	CTG	1/2"	12,5	27	13,5	41,5	21	50
RQG1-C 1/2 AD21,2 NERI	21,2	CTG	1/2"	16	29,5	13	45,5	27	50
RQG1-C 3/4 AD28,5 NERI	28,5	CTG	3/4"	20,5	37	13	48	34	25
RQG1-C 1 AD34,5 NERI	34,5	CTG	1"	25,5	44	16	52	40	25
RQG1-C 1 1/4 AD42,5 NERI	42,5	CTG	1 1/4"	35	52	18	56,5	49	25
RQG1-C 1 1/2 AD54,5 NERI	54,5	CTG	1 1/2"	40	64	14	54	59	10
RQG1-C 2 AD54,5 NERI	54,5	CTG	2"	49	64	18	58	60	10

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

