



IP 66 PLASTIC FITTINGS (PG THREAD)

Material: polyamide.

Color: gray, black.

Use temperature: -40°C / +120°C

IP protection: IP 66.

Flammability: flame retardant and self-extinguishing UL94-V0.

Regulations and Certifications: VDE (EN/IEC 61386-23), c-UR-us (file n. E86359, per le misure AD13-AD54,5), NFPA 130, LLOYD'S REGISTER, GOST.

Features: these fittings ensure excellent mechanical, tear-proof and anti-vibration resistance and guarantee IP 66 protection thanks to the conical internal structure.

They are resistant to oils, petrol and in particular to acids and solvents. Good UV resistance for black fittings. They do not contain cadmium, silicone or halogens. With PG thread - DIN 40430.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQG1-P 7 AD10 GRIGI	Grey	10	PG	7	7	17	10	32,5	16	50
RQG1-P 7 AD10 NERI	black	10	PG	7	7	17	10	32,5	16	50
RQG1-P 9 AD10 NERI	black	10	PG	9	7	18,5	10	32,5	16	50
RQG1-P 11 AD10 NERI	black	10	PG	11	7	21	10	32,5	16	50
RQG1-P 13,5 AD10 GRIGI	Grey	10	PG	13,5	7	23	10	32,5	16	25
RQG1-P 13,5 AD10 NERI	black	10	PG	13,5	7	23	10	32,5	16	25
RQG1-P 7 AD13 GRIGI	Grey	13	PG	7	8	20	10	35	18	50
RQG1-P 7 AD13 NERI	black	13	PG	7	8	20	10	35	18	50
RQG1-P 9 AD13 GRIGI	Grey	13	PG	9	10	20	10	35	18	50
RQG1-P 9 AD13 NERI	black	13	PG	9	10	20	10	35	18	50
RQG1-P 11 AD13 NERI	black	13	PG	11	10	21	10	35	18	50
RQG1-P 13,5 AD13 GRIGI	Grey	13	PG	13,5	10	23	10	35	18	25

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQG1-P 13,5 AD13 NERI	black	13	PG	13,5	10	23	10	35	18	25
RQG1-P 11 AD15,8 GRIGI	Grey	15,8	PG	11	12,5	23	10	37	21	50
RQG1-P 11 AD15,8 NERI	black	15,8	PG	11	12,5	23	10	37	21	50
RQG1-P 13,5 AD15,8 NERI	black	15,8	PG	13,5	12,5	23	10	37	21	25
RQG1-P 16 AD15,8 NERI	black	15,8	PG	16	12,5	26,5	10	37	21	25
RQG1-P 13,5 AD18,5 GRIGI	Grey	18,5	PG	13,5	13,5	26	13	43	24	50
RQG1-P 13,5 AD18,5 NERI	black	18,5	PG	13,5	13,5	26	13	43	24	50
RQG1-P 13,5 AD21,2 GRIGI	Grey	21,2	PG	13,5	15,4	29,5	13	43,5	27	50
RQG1-P 13,5 AD21,2 NERI	black	21,2	PG	13,5	15,4	29,5	13	43,5	27	10
RQG1-P 16 AD21,2 GRIGI	Grey	21,2	PG	16	17	29,5	13	46	27	50
RQG1-P 16 AD21,2 NERI	black	21,2	PG	16	17	29,5	13	46	27	50
RQG1-P 16 AD28,5 GRIGI	Grey	28,5	PG	16	17	37	12	48,5	34	10
RQG1-P 16 AD28,5 NERI	black	28,5	PG	16	17	37	12	48,5	34	10
RQG1-P 21 AD28,5 GRIGI	Grey	28,5	PG	21	23,5	37	13	48,5	34	25
RQG1-P 21 AD28,5 NERI	black	28,5	PG	21	23,5	37	13	48,5	34	25
RQG1-P 29 AD34,5 GRIGI	Grey	34,5	PG	29	30	44	14,5	53,5	40	25

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQG1-P 29 AD34,5 NERI	black	34,5	PG	29	30	44	14,5	53,5	40	25
RQG1-P 36 AD42,5 GRIGI	Grey	42,5	PG	36	36,5	51,5	14,5	56	48	25
RQG1-P 36 AD42,5 NERI	black	42,5	PG	36	36,5	51,5	14,5	56	48	25
RQG1-P 48 AD54,5 GRIGI	Grey	54,5	PG	48	48	65,5	15,5	58	59	10
RQG1-P 48 AD54,5 NERI	black	54,5	PG	48	48	65,5	15,5	58	59	10

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

