



## RACCORDI IN PLASTICA IP 68/IP 69 (FILETTO PG)

### ITEM: RQG-P 11 AD13 NERI

Codice EZ: 157639, RACCORDI Flexa code: 15020027204.

Material: body in polyamide, internal gasket in TPE.

Color: gray, black.

Use temperature: -40°C / +120°C

IP protection: IP 68, IP 69.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-UR-us (file n. E86359, per le misure AD13-AD54,5), DB, SNCF, EN 45545-2 (HL 2), NFPA 130, LLOYD'S REGISTER, GOST, TÜV VD/GGVSEB.

Features: these fittings ensure excellent mechanical, tear-proof and anti-vibration resistance and guarantee IP 68 and IP 69 protection for maximum pressurized water tightness. They are resistant to oils, petrol and in particular to acids and solvents. Good UV resistance for black fittings. They do not contain cadmium, silicone or halogens. With PG thread - DIN 40430.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                  | Color | OD tube AD | thread pitch | thread value | ØA mm | ØB mm | F mm | H mm | key mm | pack pcs. |
|-----------------------|-------|------------|--------------|--------------|-------|-------|------|------|--------|-----------|
| RQG-P 11<br>AD13 NERI | black | 13         | PG           | 11           | 10    | 21    | 10   | 35   | 18     | 50        |

\* For a better seal on the pipe in both static and dynamic applications, the following improvements have been made to this fitting: wider and trapezoidal shaped locking teeth, larger internal TPE gasket, longer pipe insertion length.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

#### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

