



PLASTIC FITTINGS WITH METAL THREAD IP 68/IP 69K (METRIC THREAD)

Material: body in polyamide 6, internal gasket in TPE, thread in nickel-plated brass.

Color: gray, black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102, I3/F2), EN 45545-2 (HL 3), LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The metal thread gives the fittings greater resistance to mechanical stress and maximum tightness when tightening both when they are mounted with the lock nut and when they are mounted directly on the structure. The thread is internally coated in plastic to give maximum insulation to the cables. They are available with PG, Metric thread. They are resistant to oils, petrol and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	Color	OD tube AD	thread pitch	thread value	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQGK-M 12 AD10 NERI	black	10	Metric	12x1.5	7	20	10	38,5	18	50
RQGK-M 12 AD10 GRIGI FC*	Grey	10	Metric	12x1.5	7	20	5	33,5	18	50
RQGK-M 12 AD10 NERI FC*	black	10	Metric	12x1.5	7	20	5	33,5	18	50
RQGK-M 12 AD13 NERI	black	13	Metric	12x1.5	7	24	10	40	22	50
RQGK-M 12 AD13 GRIGI FC*	Grey	13	Metric	12x1.5	7	24	5	35	22	50
RQGK-M 16 AD13 NERI	black	13	Metric	16x1.5	8,5	24	12	42	22	50
RQGK-M 16 AD13 GRIGI FC*	Grey	13	Metric	16x1.5	8,5	24	5	35	22	50

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQ GK-M 12 AD13 GRIGI*	Grey	13	Metric	12x1.5	7	24	10	40	22	50
RQ GK-M 12 AD13 NERI FC*	black	13	Metric	12x1.5	7	24	5	35	22	50
RQ GK-M 16 AD13 NERI FC*	black	13	Metric	16x1.5	8,5	24	5	35	22	50
RQ GK-M 16 AD15,8 NERI	black	15,8	Metric	16x1.5	10	27	12	42,5	25	50
RQ GK-M 16 AD15,8 GRIGI FC*	Grey	15,8	Metric	16x1.5	10	27	5	36,5	25	50
RQ GK-M 20 AD15,8 NERI	black	15,8	Metric	20x1.5	11	27	12	43,5	25	50
RQ GK-M 20 AD15,8 GRIGI FC*	Grey	15,8	Metric	20x1.5	11	27	6	37,5	25	50
RQ GK-M 16 AD15,8 NERI FC*	black	15,8	Metric	16x1.5	10	27	5	36,5	25	50
RQ GK-M 20 AD15,8 GRIGI****	Grey	15,8	Metric	20x1.5	11	27	12	43,5	25	50
RQ GK-M 20 AD15,8 NERI FC*	black	15,8	Metric	20x1.5	11	27	6	37,5	25	50
RQ GK-M 20 AD21,2 NERI	black	21,2	Metric	20x1.5	15	29,5	12	48	28	25
RQ GK-M 20 AD21,2 GRIGI FC*	Grey	21,2	Metric	20x1.5	15	29,5	6	44	28	25
RQ GK-M 25 AD21,2 NERI	black	21,2	Metric	25x1.5	16	33	13	49	31	25
RQ GK-M 25 AD21,2 GRIGI FC*	Grey	21,2	Metric	25x1.5	16	33	7	44	31	25
RQ GK-M 20 AD21,2 NERI FC*	black	21,2	Metric	20x1.5	15	29,5	6	44	28	25
RQ GK-M 25 AD21,2 NERI FC*	black	21,2	Metric	25x1.5	16	33	7	44	31	25

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQ GK-M 25 AD28,5 NERI	black	28,5	Metric	25x1.5	18	44	19	54	35	25
RQ GK-M 25 AD28,5 GRIGI FC*	Grey	28,5	Metric	25x1.5	18	37	7	47	35	25
RQ GK-M 32 AD28,5 NERI	black	28,5	Metric	32x1.5	20	41	14	54	39	25
RQ GK-M 32 AD28,5 GRIGI FC*	Grey	28,5	Metric	32x1.5	20	41	8	47	39	25
RQ GK-M 25 AD28,5 NERI FC*	black	28,5	Metric	25x1.5	18	37	7	47	35	25
RQ GK-M 32 AD28,5 GRIGI*	Grey	28,5	Metric	32x1.5	20	41	14	54	39	25
RQ GK-M 32 AD28,5 NERI FC*	black	28,5	Metric	32x1.5	20	41	8	48	39	25
RQ GK-M 32 AD34,5 NERI	black	34,5	Metric	32x1.5	24	44	14	57	42	25
RQ GK-M 32 AD34,5 GRIGI FC*	Grey	34,5	Metric	32x1.5	24	44	8	52	42	25
RQ GK-M 40 AD34,5 NERI	black	34,5	Metric	40x1.5	27,5	48	17	64	46	25
RQ GK-M 40 AD34,5 GRIGI FC*	Grey	34,5	Metric	40x1.5	27,5	48	8	55	46	25
RQ GK-M 32 AD34,5 NERI FC*	black	34,5	Metric	32x1.5	24	44	8	52	42	25
RQ GK-M 40 AD34,5 GRIGI*	Grey	34,5	Metric	40x1.5	27,5	48	17	61	46	25
RQ GK-M 40 AD34,5 NERI FC*	black	34,5	Metric	40x1.5	27,5	48	8	55	46	25
RQ GK-M 40 AD42,5 NERI	black	42,5	Metric	40x1.5	32	58	17	76	55	10
RQ GK-M 40 AD42,5 GRIGI FC***	Grey	42,5	Metric	40x1.5	32	58	8	67	55	10

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993





RQGK-M 50 AD42,5 NERI**	black	42,5	Metric	50x1.5	37,5	63	17	76	60	10
RQGK-M 50 AD42,5 GRIGI FC***	Grey	42,5	Metric	50x1.5	37,5	63	9	68	60	10
RQGK-M 40 AD42,5 NERI FC***	black	42,5	Metric	40x1.5	32	58	8	67	55	10
RQGK-M 50 AD42,5 GRIGI**	Grey	42,5	Metric	50x1.5	37,5	63	17	76	60	10
RQGK-M 50 AD42,5 NERI FC***	black	42,5	Metric	50x1.5	37,5	63	9	68	60	10
RQGK-M 50 AD54,5 NERI**	black	54,5	Metric	50x1.5	39	68	17	88	65	10
RQGK-M 50 AD54,5 GRIGI FC***	Grey	54,5	Metric	50x1.5	39	68	9	80	65	10
RQGK-M 63 AD 54,5 NERI**	black	54,5	Metric	63x1.5	49	74	17	88	70	10
RQGK-M 63 AD54,5 GRIGI FC***	Grey	54,5	Metric	63x1.5	49	74	10	81	70	10
RQGK-M 50 AD54,5 NERI FC***	black	54,5	Metric	50x1.5	39	68	9	80	65	10
RQGK-M 63 AD54,5 NERI FC***	black	54,5	Metric	63x1.5	49	74	10	81	70	10

* Article on request. ** For a better seal on the pipe in both static and dynamic applications, the following improvements have been made to this fitting: wider and trapezoidal shaped locking teeth, larger internal TPE gasket, longer pipe insertion length. *** Item on request. For a better seal on the pipe in both static and dynamic applications, the following improvements have been made to this fitting: wider and trapezoidal-shaped locking teeth, larger internal TPE gasket, longer pipe insertion length. **** Item available while stocks last.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)
Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

