



## PLASTIC FITTINGS WITH METAL THREAD IP 68/IP 69K (METRIC THREAD)

### ITEM: RQGK-M 63 AD 54,5 NERI

Codice EZ: 155599, PLASTIC Flexa code: 15107054263.

Material: body in polyamide 6, internal gasket in TPE, thread in nickel-plated brass.

Color: gray, black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102, I3/F2), EN 45545-2 (HL 3), LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure excellent mechanical, tear-proof and anti-vibration resistance. They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The metal thread gives the fittings greater resistance to mechanical stress and maximum tightness when tightening both when they are mounted with the lock nut and when they are mounted directly on the structure. The thread is internally coated in plastic to give maximum insulation to the cables. They are available with PG, Metric thread. They are resistant to oils, petrol and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                           | Color | OD tube AD | thread pitch | thread value | ØA mm | ØB mm | F mm | H mm | key mm | pack pcs. |
|--------------------------------|-------|------------|--------------|--------------|-------|-------|------|------|--------|-----------|
| RQGK-M 63<br>AD 54,5<br>NERI** | black | 54,5       | Metric       | 63x1.5       | 49    | 74    | 17   | 88   | 70     | 10        |

\* Article on request. \*\* For a better seal on the pipe in both static and dynamic applications, the following improvements have been made to this fitting: wider and trapezoidal shaped locking teeth, larger internal TPE gasket, longer pipe insertion length. \*\*\* Item on request. For a better seal on the pipe in both static and dynamic applications, the following improvements have been made to this fitting: wider and trapezoidal-shaped locking teeth, larger internal TPE gasket, longer pipe insertion length. \*\*\*\* Item available while stocks last.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

#### ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

