



PLASTIC FITTINGS WITH IP 66 CABLE GLAND (NPT THREAD)

Material: polyamide 6.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 66 according to EN 60529/IEC 60529 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for sizes AD21.2 to AD54.5), LLOYD'S REGISTER OF SHIPPING (suitable for use in naval and offshore applications).

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance. They guarantee IP 66 sealing thanks to the conical structure of the interior. The integrated cable gland, with internal sealing rubber, allows a waterproof and tear-resistant cable locking. They are available with PG, Metric, NPT threads.

Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	Ø est. min - max cable mm	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQGZ1-N 1/2" AD15,8 NERI	15,8	NPT	1/2"	6 - 12	12,0	27,0	15,0	69,0	21/24	50
RQGZ1-N 1/2" AD21,2 NERI	21,2	NPT	1/2"	7 - 12	12,0	29,5	15,0	73,0	27/24	25
RQGZ1-N 3/4" AD28,5 NERI	28,5	NPT	3/4"	12 - 18	18,0	37,0	15,0	79,0	34/33	25
RQGZ1-N 1" AD34,5 NERI	34,5	NPT	1"	21 - 25	25,0	44,0	18,0	89,0	40/42	10
RQGZ1-N 1 1/4 AD42,5 NERI	42,5	NPT	1" 1/4	22 - 32	32,0	52,0	18,0	100,0	49/53	10

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

