



PLASTIC FITTINGS WITH CABLE GLAND IP 68/IP 69K (NPT THREAD)

Material: body in polyamide 6, internal gasket in TPE.

Color: black.

Use temperature: -40°C / +115°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: VDE (EN/IEC 61386-23), c-CSA-us (UL 1696, valid for measurements AD21.2 to AD54.5), DB (DIN 5510 2, S1), SNCF (NFF 16-101/102, I3/F2), EN 45545-2 (HL 2), LLOYD'S REGISTER OF SHIPPING (suitability for use in naval and offshore applications).

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The integrated cable gland, with internal sealing rubber, allows a waterproof and tear-resistant cable locking. They are available with PG, Metric, NPT threads.

Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

ITEM	OD tube AD	thread pitch	thread value	Ø est. min - max cable mm	ØA mm	ØB mm	F mm	H mm	key mm	pack pcs.
RQGZ-N 1/2 AD15,8 NERI	15,8	NPT	1/2"	6 - 12	12	27	15	69	21/24	20
RQGZ-N 1/2 AD21,2 NERI	21,2	NPT	1/2"	7 - 10	12	29,5	15	73	27/24	10
RQGZ-N 3/4 AD28,5 NERI	28,5	NPT	3/4"	12 - 18	18	37	15	79	34/33	10
RQGZ-N 1 AD34,5 NERI	34,5	NPT	1"	21 - 25	25	44	18	89	40/42	10
RQGZ-N 1 1/4 AD42,5 NERI	42,5	NPT	1" 1/4	24 - 32	32	52	19	100	49/53	10

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

ELEKTROZUBEHÖR SPA

Sede:
Via F.lli Bronzetti, 24
20129 Milano (Italy)

Tel.: +39 02 701471
C.F. e P. IVA: 00729140152
Capitale Sociale: € 260.000

Centro logistico:
Via Cadorna, 66/A
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano
R.E.A.: 460657 - INTRASTAT: IT 00729140152
Posizione Import: MI 007993

