



## PLASTIC FITTINGS WITH METAL CABLE GLAND IP 68/IP 69K (METRIC THREAD)

### ITEM: RQGKZP-M 50.27.32 AD42,5 L10 NERI

**Codice EZ:** request the code from our sales office, PLASTIC Flexa code: 15112142250.

Material: fitting body in polyamide 6, internal gasket in TPE, body of the cable gland and thread in nickel-plated brass.

Color: black.

Use temperature: -50°C / +120°C

IP protection: IP 68 according to EN 60529/IEC 60529 specifications and IP 69K according to DIN 40050 T.9 specifications.

Flammability: flame retardant and self-extinguishing UL94-V0 (polyamide 6).

Regulations and Certifications: CE, VDE (EN/IEC 61386-23), DIN EN 45545-2 HL3, DIN EN 45545-3 E30 (soltanto per i raccordi RQGKZP), NFPA 130 (ASTM E162/E662, SMP 800-C), LLOYD'S REGISTER (soltanto per i raccordi RQGKZ), c-UR-us (UL 1696 / CSA 22.2; file n. E86359, per le misure AD13-AD54,5), JRMA.

Features: they ensure perfect mechanical, tear-proof and anti-vibration resistance.

They guarantee IP 68 and IP 69K protection for maximum pressurized water tightness. The integrated cable gland, with internal sealing rubber, allows a waterproof and tear-resistant cable locking. The metal thread gives the fittings maximum tightness when tightened whether they are mounted with the lock nut or mounted directly on the structure. The thread is internally coated in plastic to give maximum insulation to the cables. They are available with PG, Metric thread. Resistance to oils, gasoline and in particular to acids and solvents. They do not contain cadmium, silicone or halogens.

The drawing is indicative and the proportions may not correspond to the table or real dimensions.

| ITEM                              | specific | OD tube<br>AD | thread<br>pitch | thread<br>value | Ø est. min<br>- max<br>cable mm | ØA mm | ØB mm | F mm | H mm | key mm | pack pcs. |
|-----------------------------------|----------|---------------|-----------------|-----------------|---------------------------------|-------|-------|------|------|--------|-----------|
| RQGKZP-M 50.27.32 AD42,5 L10 NERI | RQGKZP   | 42,5          | Metric          | 50x1.5          | 27 - 32                         | 36    | 60    | 10   | 82   | 50/57  | 10        |

N.B.: se in tabella, nella colonna "chiave", vi sono due dimensioni separate da " / " (esempio: 22/17), la prima dimensione corrisponde al CORPO del raccordo, mentre la seconda alla TESTA filettata. In caso di dimensione unica, essa corrisponde ad entrambe le parti.

Tutte le informazioni e i dati sono indicativi e possono essere soggetti a variazioni senza preavviso

## ELEKTROZUBEHÖR SPA

**Sede:**  
Via F.lli Bronzetti, 24  
20129 Milano (Italy)

Tel.: +39 02 701471  
C.F. e P. IVA: 00729140152  
Capitale Sociale: € 260.000

**Centro logistico:**  
Via Cadorna, 66/A  
20055 Vimodrone MI

Registro imprese: n° 92394 Tribunale di Milano  
R.E.A.: 460657 - INTRASTAT: IT 00729140152  
Posizione Import: MI 007993

